

The background of the cover features a dark, high-contrast image of a motorcycle, likely a scooter, with a strong red light source creating a dramatic, low-key effect. The light highlights the contours of the vehicle, particularly the front fairing and handlebars, while the rest of the bike and the background are in deep shadow. The overall mood is sleek, modern, and high-tech.

QJMOTOR

**PRODUCT
CATALOG
2024**



QIANJIANG MOTORCYCLE INTRODUCTION

Qianjiang Motorcycle Co., Ltd., established in 1985 and located in Wenling, Zhejiang, is an enterprise under Geely technology group, whose main business is research and development, manufacturing, and sales of motorcycles, engines, and parts. Qianjiang was listed on Shenzhen Stock Exchange in 1999 (Stock Code: 000913). Qianjiang is also the first listed company in Taizhou.

Qianjiang successfully acquired Italy Benelli in 2005, becoming the first Chinese motorcycle manufacturer to merge an international motorcycle brand. Qianjiang thereafter produces higher displacement engine motorcycles to meet the market needs for high-end cruiser and racing replica. Qianjiang has been the leader in the segment of motorcycles over 250cc for 12 consecutive years in China. In 2020 Qianjiang launched a new high-end brand QJMOTOR. Up to now Qianjiang owns 3 brands- QJANG, BENELLI, and QJMOTOR. Each brand has its unique positioning to meet the diversified market needs. Besides, Qianjiang is one of the few motorcycle manufacturers in China capable to design and produce high-end motorcycles with higher engine displacement. Qianjiang keeps over 6,000 employees and exports to over 130 countries in the world.

QJMOTOR BRAND INTRODUCTION

Right after realizing the strategic blueprint and brand upgrade, Qianjiang Motorcycle, under Geely Technology Group, launched a new high-end brand QJMOTOR, aiming to produce more intelligent and humanized vehicles for better riding experience and fun. QJMOTOR aspires to be a leader in the global smart motorcycle industry.

QJMOTOR Brand Vision : ALWAYS FORWARD

QJMOTOR Brand Value

Forward: Blow the horn of advance to drive the future.

Power: Unrivalled driving force to conquer afar.

Prospect: Unlimited possibilities to make the dreams come true.

Fun: Riding is fun and full of enjoyments.

Sincere: Worry-free service brings us together as a family.

QJMOTOR Brand DNA

Perseverance

Breakthrough

Self-Confidence

Passion

QJMOTOR+

High Cost Performance

We emphasize value over price. QJMOTOR's design concept is to meet the needs of younger generation for better value-for-money consumption, offering to the younger generation more affordable big motorcycles made with the world class Chinese intelligent manufacturing.

Ultimate Experience

In terms of buying, we offer online query, offline delivery, and convenient payment

In terms of service, we offer complete after-sales package, guaranteeing worry-free experience for each user

In terms of social networking, we offer customized CLUB culture, organizing riding tours for the best enjoyment.



QJMOTOR



SRK Series

- 02 SRK 900(QJ900-2C)
- 03 SRK 800(QJ800-H)
- 04 SRK 700(QJ700-8A)
- 05 SRK 600 A(QJ600GS-3A)
- 06 SRK 600(QJ500-7B)
- 07 SRK 500 C(QJ400-16)
- 08 SRK 400(QJ400-13A)
- 09 SRK 300 S(QJ300-29D)
- 10 SRK 250(QJ250-13)
- 11 SRK 250 S(QJ250-29D)
- 12 SRK 180 S(QJ175-31B)
- 13 SRK 125 D (QJ125-29H)
- 14 SRK 125 S(QJ125-31B)
- 15 SRK 125 E(QJ125-7E)
- 16 SRF 12(QJ125-3G)



SRK Racing Series

- 18 SRK 921 RR(QJ900GS-8D)
- 19 SU 9(QJ900GS-8F)
- 20 SRK 800 RR(QJ800GS-G)
- 21 SRK 600 RC(QJ600GS-3D)
- 22 SRK 600 RS(QJ500GS-7A)
- 23 SRK 500 RC(QJ400GS-16D)
- 24 SRK 450 RR(QJ400GS-16R)
- 25 SRK 400 RR(QJ400GS-J)
- 26 SRK 400 RR(QJ400GS-G)
- 27 SRK 250 RS(QJ250GS-29E)
- 28 SRK 250 RC(QJ250GS-16D)
- 29 SRK 25 R(QJ250GS-29F)
- 30 SRK 125 R(QJ125GS-29F)



SRT Series

- 32 SRT 900 SX(QJ900-7E)
- 33 SRT 900 S(QJ900-7E)
- 34 SRT 800 SX(QJ800-7B)
- 35 SRT 800 S(QJ800-7B)
- 36 SRT 700 X(QJ700-5J)
- 37 SRT 700(QJ700-5J)
- 38 SRT 700 SX(QJ700-5S)
- 39 SRT 700 S(QJ700-5S)
- 40 SVT 650 X(QJ650-16A)
- 41 SVT 650(QJ650-16A)
- 42 SRT 600 SX(QJ500-7C)
- 43 SRT 600 S(QJ500-7C)
- 44 SRT 600 X(QJ500-5R)
- 45 SRT 600(QJ500-5P)
- 46 SRT 500 RX(QJ400-7H)



SRV Series

- 48 SRV 700(QJ700-11A)
- 49 SRV 600 ST(QJ500-11C/D)
- 50 SRV 600 V(QJ600-12B)
- 51 SRV 600 V2(QJ600-12L)
- 52 SRV 400 VS(QJ400-12K)
- 53 SRV 350 VS(QJ350-12E)
- 54 SRV 300 A(QJ300-12N)
- 55 SRV 300(QJ300-12A)
- 56 SRV 250(QJ250-12A)
- 57 SRV 200(QJ200-2L)
- 58 SRV 125(QJ125-2K)
- 59 SRV 12(QJ125-12H)
- 60 SRV 600(QJ500-19)
- 61 SRC 400(QJ400-8C)
- 62 SRV 249(QJ250-19)
- 63 SRC 250(QJ250-9)

CONTENTS

● QJMOTOR models may have different specific ations to comply with local regulations, and maybe modified to meet specific demands in a particular region.



Scooter Series

- 65 FORT 400/4.0(QJ350T-2D)
- 66 FORT 250(QJ250T-9A)
- 67 FORT 250(QJ250T-9D)
- 68 MTX 250(QJ250T-23N)
- 69 MTX 200(QJ175T-23H)
- 70 ATR 200(QJ175T-23F)
- 71 AX 200 S(QJ175T-23P)
- 72 SQ 20(QJ175T-30E)
- 73 RKO 150 W(QJ150T-6W)
- 74 RKO 150 Y(QJ150T-6Y)
- 75 LTR 150 K(QJ125T-27K)
- 76 RKO 125 W(QJ125T-6W)
- 77 RKO 125 S(QJ125T-6J)
- 78 RKO 125 P(QJ125T-6P)
- 79 MTX 125(QJ125T-23H)
- 80 ATR 125(QJ125T-23F)
- 81 FORT 125 N(QJ125T-5M)
- 82 LTR 125(QJ125T-27J)
- 83 LTS 125 S(QJ125T-13C)
- 84 SQ 16(QJ125T-30E)

- 85 LTR 50(QJ50T-27E)
- 86 LTR 50 S(QJ50T-13C)

Commuter Series

- 88 TRX 25(QJ250-29K)
- 89 TRX 12(QJ125-29K)
- 90 KPV 200 U(QJ175-6B)
- 91 NX 200 X(QJ175-26U)
- 92 NX 150(QJ150-26E)
- 93 NX 150 X(QJ150-26U)
- 94 KPV 152(QJ150-6C)

Electric Series

- 96 OMO 07(QJ10000DT)
- 97 OMO 03(QJ5000DT-3)
- 98 OAO(QJ5000D)
- 99 OAO-PRO(QJ5000D-A)
- 100 MOk
- 101 Q2(QJ3000DT-7)
- 102 G2(QJ3000DT-3)

- 103 OMO-01+(QJ3000DT-3B)
- 104 OMO-01C(QJ3000DT-3C)
- 105 ELT-27 E(QJ3000DT-27E)
- 106 ELT-27 K(QJ3000DT-27K)
- 107 E-LTS(QJ3000DT-13C)
- 108 E-KVP(QJ3000D-2)
- 109 TQ(QJ1500DT-5A)
- 110 DQ(QJ1000DT-7)
- 111 BQ(QJ800DQT-D)
- 112 V1(TDT030Z)
- 113 V2(TDT031Z)
- 114 V3(TDT040Z)
- 115 VO(TDT007Z/TDT008Z)
- 116 VC(TDT024Z/TDT047Z)
- 117 VC+(TDT042Z/TDT059Z)
- 118 S2(TDR068Z/TDR027Z)
- 119 S3(TDR028Z)
- 120 S5(TDR029Z)
- 121 S6(TDT041Z)
- 122 MOi(TDR006Z)

- 123 OMO 07 J(QJ10000DTJ)
For police use
- 124 OMO 03 J(QJ5000DTJ-3)
For police use
- 125 RainBOW

SFT Series

- 127 SFT 900(QJ900B)
- 128 SFT 600(QJ500B-A)
- 129 SFT 400(QJ350B-B)
- 130 SFT 300(QJ350B)

Four Wheel Series

- 132 SFA 1000(QJ1000A-A)
- 133 SFA 600(QJ600A-A)
- 134 SFA 500(ATV 500)
- 135 SFA 300(ATV 300)
- 136 SFV 1000(QJ1000US)
- 137 SFU 1000 R(QJ1000UU-A)
- 138 SFU 1000 F(QJ1000UU)

QJMOTOR

SRK Series



QJMOTOR

SRK 900 (QJ900-2C)

SPORT NAKED



Engine

Type	2-Cylinder, 8V DOHC, Liquid-cooled
Bore*Stroke	92.0*68.0mm
Displacement	904cc
Max.Horsepower	70.0KW/9000RPM
MAX.Torque	90.0NM/6500RPM
Fuel system	EFI
Starting system	Electric
Clutch	Wet multi-plate
Transmission	6 Gears, Chain

Chassis

Front suspension	Upside down telescopic forks
Rear suspension	Telescopic coil spring oil damped
Front tyre	120/70 R17
Rear tyre	180/55 R17
Front brake	Disc ø320mm
Rear brake	Disc ø260mm

Dimensions

Overall L*W*H	2100*840*1170mm
Wheel base	1460mm
Seat height	810mm
Ground clearance	180mm
Curb weight	220kg
Fuel capacity	17.8L

Available Colours:   

Homologation: E5+

QJMOTOR

SRK 800 (QJ800-H)

SPORT NAKED



Engine(High power version)

Type	4-Cylinder, 16V DOHC, Liquid-Cooled
Bore*Stroke	67.0*55.2mm
Displacement	778cc
Max.Horsepower	90.0KW/12000RPM (high power)
MAX.Torque	74.0NM/9500RPM
Fuel system	EFI
Starting system	Electric
Clutch	Wet multi-plate
Transmission	6 Gears, Chain

Chassis

Front suspension	Upside down telescopic forks
Rear suspension	Telescopic coil spring oil damped
Front tyre	120/70 ZR17
Rear tyre	180/55 R17
Front brake	Disc ø320mm
Rear brake	Disc ø260mm

Dimensions

Overall L*W*H	2085*770*1150mm
Wheel base	1450mm
Seat height	815mm
Ground clearance	150mm
Curb weight	207kg
Fuel capacity	17.5L

Available Colours:   

Homologation: E5+

QJMOTOR

SRK 700 (QJ700-8A)

SPORT NAKED



Engine

Type	2-Cylinder Inline, 8V DOHC, Liquid-Cooled
Bore*Stroke	83.0*64.5mm
Displacement	698cc
Max.Horsepower	54.0KW/8000RPM (35.0KW/6500r/min)
MAX.Torque	67.0NM/6000RPM (58.0NM/5250r/min)
Fuel system	EFI
Starting system	Electric
Clutch	Manual, multilate Wet Clutch
Transmission	6 Gears, Chain

Chassis

Front suspension	Telescopic Upside-Down
Rear suspension	Telescopic coil spring oil damped
Front tyre	120/70ZR17
Rear tyre	160/60ZR17
Front brake	Hydr.Disc ø320mm(double)(ABS)
Rear brake	Hydr.Disc ø260mm(ABS)

Dimensions

Overall L*W*H	2070*790*1130mm
Wheel base	1410mm
Seat height	790mm
Ground clearance	135mm
Curb weight	196kg
Fuel capacity	15.0L

Available Colours:    

Homologation: E-Mark, E5, E5+, EPA

QJMOTOR

SRK 600 A (QJ600GS-3A)

SPORT NAKED



Engine

Type	4-Cylinder Inline, 16V DOHC, Liquid-Cooled
Bore*Stroke	65.0*45.2mm
Displacement	600cc
Max.Horsepower	60.0KW/11000RPM
MAX.Torque	51.0NM/10500RPM
Fuel system	EFI
Starting system	Electric
Clutch	Manual,multilate Wet Clutch(ASC)
Transmission	6 Gears. Chain

Chassis

Front suspension	Telescopic Upside-Down
Rear suspension	Telescopic coil spring oil damped
Front tyre	120/70ZR17
Rear tyre	180/55ZR17
Front brake	Hydr.Disc ø320mm (double)(ABS)
Rear brake	Hydr.Disc ø260mm (ABS)

Dimensions

Overall L*W*H	2140*790*1080mm
Wheel base	1460mm
Seat height	800mm
Ground clearance	150mm
Curb weight	229kg
Fuel capacity	15.0L

Available Colours:       

Homologation: E-Mark

QJMOTOR

SRK 600 (QJ500-7B)

SPORT NAKED



Engine

Type	2-Cylinder,8V DOHC,Liquid-Cooled
Bore*Stroke	70.5*71.0mm
Displacement	554cc
Max.Horsepower	41.2KW/8250RPM
MAX.Torque	54.0NM/5500RPM
Fuel system	EFI
Starting system	Electric
Clutch	Wet multi-plate
Transmission	6 Gears,Chain

Chassis

Front suspension	Telescopic Upside-Down
Rear suspension	Telescopic coil spring oil damped
Front tyre	120/70ZR17
Rear tyre	160/60ZR17
Front brake	Disc ø320mm(double)(ABS)
Rear brake	Disc ø260mm(ABS)

Dimensions

Overall L*W*H	2100*865*1165mm
Wheel base	1420mm
Seat height	810/790mm
Ground clearance	160mm
Curb weight	176kg
Fuel capacity	15L

Available Colours:   

Homologation: E5,E5+

QJMOTOR

SRK 500 C (QJ400-16)

SPORT NAKED



Engine

Type	2-Cylinder, 8V DOHC, Liquid-Cooled
Bore*Stroke	70.0*58.4mm
Displacement	449cc
Max.Horsepower	39.0KW/9500RPM
MAX.Torque	43.0NM/8000RPM
Fuel system	EFI
Starting system	Electric
Clutch	Wet multi-plate
Transmission	6 Gears,Chain

Chassis

Front suspension	Telescopic Upside-Down
Rear suspension	Telescopic coil spring oil damped
Front tyre	110/70R17
Rear tyre	150/60R17
Front brake	Disc ø320mm (ABS)
Rear brake	Disc ø240mm (ABS)

Dimensions

Overall L*W*H	2030*750*1150mm
Wheel base	1380mm
Seat height	785mm
Ground clearance	135mm
Curb weight	173kg
Fuel capacity	14.8L

Available Colours:   

Homologation: E5

QJMOTOR

SRK 400 (QJ400-13A)

SPORT NAKED



Engine

Type	2-Cylinder Inline, 8V DOHC, Liquid-Cooled
Bore*Stroke	70.5*51.2mm
Displacement	400cc
Max.Horsepower	30.5KW/9000RPM
MAX.Torque	37.0NM/7500RPM
Fuel system	EFI
Starting system	Electric
Clutch	Manual,multilate Wet Clutch
Transmission	6 Gears, Chain

Chassis

Front suspension	Telescopic Upside-Down
Rear suspension	Telescopic coil spring oil damped
Front tyre	110/70 R17 M/C
Rear tyre	150/60 R17 M/C
Front brake	Hydr.Disc ø260mm (double)(ABS)
Rear brake	Hydr.Disc ø240mm (ABS)

Dimensions

Overall L*W*H	2080*820*1085/1100mm
Wheel base	1425mm
Seat height	785mm
Ground clearance	150mm
Curb weight	186kg
Fuel capacity	13.5L

Available Colours:     

Homologation: E5

QJMOTOR

SRK 300 S (QJ300-29D)

SPORT NAKED



Engine

Type	1-Cylinder, 4V DOHC, Liquid-Cooled
Bore*Stroke	78.0*61.2mm
Displacement	292.3cc
Max.Horsepower	21.5KW/9000RPM
MAX.Torque	24.5NM/7000RPM
Fuel system	EFI
Starting system	Electric
Clutch	Wet multi-plate
Transmission	6 Gears, Chain

Chassis

Front suspension	Upside down telescopic forks
Rear suspension	Telescopic coil spring oil damped
Front tyre	110/70 R17
Rear tyre	150/60 R17
Front brake	Disc ø300mm
Rear brake	Disc ø240mm

Dimensions

Overall L*W*H	2010*810*1070mm
Wheel base	1370mm
Seat height	785mm
Ground clearance	120mm
Curb weight	162kg
Fuel capacity	12.5±0.5L

Available Colours:   

Homologation: E5+

QJMOTOR

SRK 250 (QJ250-13)

SPORT NAKED



Engine

Type	2-Cylinder Inline, 8V DOHC, Liquid-Cooled
Bore*Stroke	61.0*42.7mm
Displacement	249.6cc
Max.Horsepower	23.5KW/11000RPM
MAX.Torque	21.2NM/9000RPM
Fuel system	EFI
Starting system	Electric
Clutch	Wet multiplate with ASC
Transmission	6 Gears, Chain

Chassis

Front suspension	Telescopic Upside-Down
Rear suspension	Telescopic coil spring oil damped
Front tyre	110/70 R17
Rear tyre	140/70 R17 or 150/60 R17
Front brake	Disc ø300mm (ABS)
Rear brake	Disc ø240mm (ABS)

Dimensions

Overall L*W*H	2080*820*1085mm
Wheel base	1425mm
Seat height	785mm
Ground clearance	150mm
Curb weight	186kg
Fuel capacity	13.5L

Available Colours:     

Homologation: E-Mark, E5, E5+

QJMOTOR

SRK 250 S (QJ250-29D)

SPORT NAKED



Engine

Type	1-Cylinder, Liquid-Cooled
Bore*Stroke	72.0*61.2mm
Displacement	249.22cc
Max.Horsepower	20.5KW/9500RPM
MAX.Torque	22.5NM/7250RPM
Fuel system	EFI
Starting system	Electric
Clutch	Wet multi-plate
Transmission	6 Gears, Chain

Chassis

Front suspension	Telescopic Upside-Down
Rear suspension	Telescopic coil spring oil damped
Front tyre	110/60 R17
Rear tyre	140/60 R17
Front brake	Disc ø300mm
Rear brake	Disc ø240mm

Dimensions

Overall L*W*H	2010*810*1070mm
Wheel base	1370mm
Seat height	780mm
Ground clearance	135mm
Curb weight	160kg
Fuel capacity	12.5L

Available Colours:    

Homologation: E5+

QJMOTOR

SRK 180 S (QJ175-31B)

SPORT NAKED



Engine

Type	1-Cylinder, 2V SOHC, Liquid-Cooled
Bore*Stroke	64.0*54.5mm
Displacement	175.3cc
Max.Horsepower	13.3KW/9500RPM
MAX.Torque	15.2NM/6000RPM
Fuel system	EFI
Starting system	Electric
Clutch	Wet multi-plate
Transmission	Chain

Chassis

Front suspension	Telescopic Upside down
Rear suspension	Telescopic coil spring oil damped
Front tyre	100/80-17
Rear tyre	130/70-17
Front brake	Disc ø280mm
Rear brake	Disc ø220mm

Dimensions

Overall L*W*H	1970*785*1070mm
Wheel base	1345mm
Seat height	790mm
Ground clearance	200mm
Curb weight	143kg
Fuel capacity	10.0±0.5L

Available Colours:   

Homologation: E-Mark, E5+

QJMOTOR

SRK 125 D (QJ125-29H)

SPORT NAKED



Engine

Type	1-Cylinder, SOHC, Liquid-Cooled
Bore*Stroke	54.0*54.5mm
Displacement	125cc
Max.Horsepower	11.0KW/9500RPM
MAX.Torque	12.0NM/7000RPM
Fuel system	EFI
Starting system	Electric
Clutch	Wet multi-plate
Transmission	6 Gears, Chain

Chassis

Front suspension	Upside down telescopic forks
Rear suspension	Telescopic coil spring oil damped
Front tyre	110/60 R17
Rear tyre	140/60 R17
Front brake	Disc
Rear brake	Disc

Dimensions

Overall L*W*H	2010*802*1110mm
Wheel base	1360mm
Seat height	780mm
Ground clearance	135mm
Curb weight	140kg
Fuel capacity	12.5L

Available Colours:   

Homologation: E5+

QJMOTOR

SRK 125 S (QJ125-31B)

SPORT NAKED



Engine

Type	1-Cylinder,4V SOHC,Liquid-Cooled
Bore*Stroke	54.0*54.5mm
Displacement	125cc
Max.Horsepower	11.0KW/9500RPM
MAX.Torque	12.0NM/7000RPM
Fuel system	EFI
Starting system	Electric
Clutch	Manual,multilate Wet Clutch
Transmission	6 Gears, Chain

Chassis

Front suspension	Telescopic Upside-Down
Rear suspension	Telescopic coil spring oil damped
Front tyre	100/80-17
Rear tyre	130/70-17
Front brake	Hydr.Disc ø260mm (ABS)
Rear brake	Hydr.Disc ø240mm (ABS)

Dimensions

Overall L*W*H	1970*785*1070mm
Wheel base	1345mm
Seat height	790mm
Ground clearance	190mm
Curb weight	143kg
Fuel capacity	10.0L

Available Colours:    

Homologation: E5,E5+

QJMOTOR

SRK 125 E (Q125-7E)

SPORT NAKED



Engine

Type	1-Cylinder, SOHC, Air-cooled
Bore*Stroke	52.5*57.4mm
Displacement	124cc
Max.Horsepower	6.9KW/7500RPM
MAX.Torque	9.8NM/6000RPM
Fuel system	EFI
Starting system	Electric
Clutch	Automatic CVT
Transmission	6 Gears, Belt

Chassis

Front suspension	Upside down telescopic forks
Rear suspension	Telescopic coil spring oil damped
Front tyre	90/90-12
Rear tyre	100/90-10
Front brake	Disc ø190mm
Rear brake	Disc ø190mm

Dimensions

Overall L*W*H	1750*735*1000mm
Wheel base	1300mm
Seat height	760mm
Ground clearance	140mm
Curb weight	113kg
Fuel capacity	9L

Available Colours:   

Homologation: /

QJMOTOR

SRF 12 (QJ125-3G)

SPORT NAKED



Engine

Type	1-Cylinder,4V SOHC,Air-Cooled
Bore*Stroke	54.0*54.5mm
Displacement	125cc
Max.Horsepower	8.2KW/9500RPM
MAX.Torque	10.0NM/7000RPM
Fuel system	EFI
Starting system	Electric
Clutch	Manual,multilate Wet Clutch
Transmission	5 Gears, Chain

Chassis

Front suspension	Telescopic Upside-Down
Rear suspension	Telescopic coil spring oil damped
Front tyre	120/70-12
Rear tyre	130/70-12
Front brake	Hydr.Disc ø220mm (ABS)
Rear brake	Hydr.Disc ø210mm (ABS)

Dimensions

Overall L*W*H	1770*760*1025mm
Wheel base	1215mm
Seat height	760mm
Ground clearance	160mm
Curb weight	124kg
Fuel capacity	7.2L

Available Colours:   

Homologation: 150: E-Mark
125: E5,EPA

QJMOTOR

SRK Racing Series



QJMOTOR

SRK 921 RR (QJ900GS-8D)

SPORT RACING



Engine(High power version)

Type	4-Cylinder, 16V DOHC, Liquid cooled with oil radiator
Bore*Stroke	78.0*48.2mm
Displacement	921cc
Max.Horsepower	120.0KW/13600RPM (high power)
MAX.Torque	90.0NM/11000RPM
Fuel system	EFI
Starting system	Electric
Clutch	Wet multi-plate
Transmission	6 Gears, Chain

Chassis

Front suspension	Upside down telescopic forks
Rear suspension	Telescopic coil spring oil damped
Front tyre	120/70 ZR17
Rear tyre	190/50 ZR17
Front brake	Disc ø320mm
Rear brake	Disc ø260mm

Dimensions

Overall L*W*H	2085*790*1130mm
Wheel base	1425mm
Seat height	835mm
Ground clearance	130mm
Curb weight	223kg
Fuel capacity	16L

Available Colours:   

Homologation: E-Mark,E5+

QJMOTOR

SU 9 (QJ900GS-8F)

// SPORT RACING



Engine

Type	4-Cylinder, 16V DOHC, Liquid cooled
Bore*Stroke	73.0*55.0mm
Displacement	921cc
Max.Horsepower	95.0KW/10000RPM
MAX.Torque	93.0NM/8000RPM
Fuel system	EFI
Starting system	Electric
Clutch	Wet multi-plate
Transmission	6 Gears, Chain

Chassis

Front suspension	Upside down telescopic forks
Rear suspension	Telescopic coil spring oil damped
Front tyre	120/70 ZR17
Rear tyre	190/50 ZR18
Front brake	Disc ø320mm
Rear brake	Disc ø260mm

Dimensions

Overall L*W*H	2090*790*1140mm
Wheel base	1425mm
Seat height	835mm
Ground clearance	145mm
Curb weight	220kg
Fuel capacity	15L

Available Colours:   

Homologation: /

QJMOTOR

SRK 800 RR (QJ800GS-G)

SPORT RACING



Engine(High power version)

Type	4-Cylinder, 16V DOHC, Liquid-Cooled
Bore*Stroke	67.0*55.2mm
Displacement	778cc
Max.Horsepower	90.0KW/12000RPM (high power)
MAX.Torque	74.0NM/9500RPM
Fuel system	EFI
Starting system	Electric
Clutch	Wet multi-plate
Transmission	6 Gears, Chain

Chassis

Front suspension	Upside down telescopic forks
Rear suspension	Telescopic coil spring oil damped
Front tyre	120/70 R17
Rear tyre	180/55 R17
Front brake	Disc ø320mm
Rear brake	Disc ø260mm

Dimensions

Overall L*W*H	2085*770*1130mm
Wheel base	1450mm
Seat height	815mm
Ground clearance	130mm
Curb weight	214kg
Fuel capacity	16L

Available Colours:   

Homologation: E-Mark,E5,E5+

QJMOTOR

SRK 600 RC (QJ600GS-3D)

SPORT RACING



Engine

Type	4-Cylinder Inline, 16V DOHC, Liquid-Cooled
Bore*Stroke	65.0*45.2mm
Displacement	600cc
Max.Horsepower	60.0KW/11000RPM
MAX.Torque	51.0NM/10500RPM
Fuel system	EFI
Starting system	Electric
Clutch	Manual,multilate Wet Clutch(ASC)
Transmission	6 Gears, Chain

Chassis

Front suspension	Telescopic Upside-Down
Rear suspension	Telescopic coil spring oil damped
Front tyre	120/70ZR17
Rear tyre	180/55ZR17
Front brake	Hydr.Disc ø320mm (double)(ABS)
Rear brake	Hydr.Disc ø260mm (ABS)

Dimensions

Overall L*W*H	2140*750*1150mm
Wheel base	1460mm
Seat height	800mm
Ground clearance	140mm
Curb weight	225kg
Fuel capacity	16.4L

Available Colours: 

Homologation: E-Mark

QJMOTOR

SRK 600 RS (QJ500GS-7A)

SPORT RACING



Engine

Type	2-Cylinder,8V DOHC,Liquid-Cooled
Bore*Stroke	70.5*71.0mm
Displacement	554cc
Max.Horsepower	41.2KW/8250RPM
MAX.Torque	54.0NM/5500RPM
Fuel system	EFI
Starting system	Electric
Clutch	Wet multi-plate
Transmission	6 Gears,Chain

Chassis

Front suspension	Telescopic Upside-Down
Rear suspension	Telescopic coil spring oil damped
Front tyre	120/70ZR17
Rear tyre	160/60ZR17
Front brake	Disc ø320mm(double)(ABS)
Rear brake	Disc ø260mm(ABS)

Dimensions

Overall L*W*H	2090*770*1155mm
Wheel base	1420mm
Seat height	770/790mm
Ground clearance	140mm
Curb weight	194kg
Fuel capacity	16.5L

Available Colours:    

Homologation: E5,E5+

QJMOTOR

SRK 500 RC (QJ400GS-16D)

SPORT RACING



Engine

Type	2-Cylinder Inline, 8V DOHC, Liquid-Cooled
Bore*Stroke	70.0*58.4mm
Displacement	449cc
Max.Horsepower	39.0KW/9500RPM
MAX.Torque	43.0NM/8000RPM
Fuel system	EFI
Starting system	Electric
Clutch	Wet multi-plate
Transmission	6 Gears,Chain

Chassis

Front suspension	Telescopic Upside-Down
Rear suspension	Telescopic coil spring oil damped
Front tyre	110/70R17
Rear tyre	150/60R17
Front brake	Hydr.Disc ø300mm(double)(ABS)
Rear brake	Hydr.Disc ø240mm(ABS)

Dimensions

Overall L*W*H	2030*750*1150mm
Wheel base	1380mm
Seat height	785mm
Ground clearance	135mm
Curb weight	173kg
Fuel capacity	14.5L

Available Colours:    

Homologation: E5+

QJMOTOR

SRK 450 RR (QJ400GS-16R)

SPORT RACING



Engine

Type	4-Cylinder, 16V DOHC, Liquid-Cooled
Bore*Stroke	57.0*41.2mm
Displacement	421cc
Max.Horsepower	57.0KW/14000RPM
MAX.Torque	39.0NM/13000RPM
Fuel system	EFI
Starting system	Electric
Clutch	Wet multi-plate
Transmission	6 Gears, Chain

Chassis

Front suspension	Upside down telescopic forks
Rear suspension	Telescopic coil spring oil damped
Front tyre	120/70 ZR17
Rear tyre	160/60 ZR17
Front brake	Disc ø300mm
Rear brake	Disc ø240mm

Dimensions

Overall L*W*H	2020*720*1130mm
Wheel base	1375mm
Seat height	808mm
Ground clearance	150mm
Curb weight	176kg
Fuel capacity	16L

Available Colours:   

Homologation: E5+

QJMOTOR

SRK 400 RR (QJ400GS-J)

SPORT RACING



Engine

Type	2-Cylinder Inline, 8V DOHC, Liquid-Cooled
Bore*Stroke	70.5*51.2mm
Displacement	400cc
Max.Horsepower	30.5KW/9000RPM
MAX.Torque	37.0 Nm/7500RPM
Fuel system	EFI
Starting system	Electric
Clutch	Manual, multilate Wet Clutch
Transmission	6 Gears, Chain

Chassis

Front suspension	Telescopic Upside-Down
Rear suspension	Telescopic coil spring oil damped
Front tyre	110/70 R17
Rear tyre	150/60 R17
Front brake	Hydr.Disc ø260mm (double)(ABS)
Rear brake	Hydr.Disc ø240mm (ABS)

Dimensions

Overall L*W*H	2030*775*1130mm
Wheel base	1420mm
Seat height	790mm
Ground clearance	140mm
Curb weight	191kg
Fuel capacity	14.3L

Available Colours:    

Homologation: 250: E-Mark
400: E5,E5+,EPA

QJMOTOR

SRK 400 RR (QJ400GS-G)

SPORT RACING



Engine

Type	2-Cylinder Inline, 8V DOHC, Liquid-Cooled
Bore*Stroke	70.5*51.2mm
Displacement	400cc
Max.Horsepower	30.5KW/9000RPM
MAX.Torque	37.0 Nm/7500RPM
Fuel system	EFI
Starting system	Electric
Clutch	Manual,multilate Wet Clutch
Transmission	6 Gears, Chain

Chassis

Front suspension	Telescopic Upside-Down
Rear suspension	Telescopic coil spring oil damped
Front tyre	110/70 R17
Rear tyre	150/60 R17
Front brake	Hydr.Disc ø260mm (double)(ABS)
Rear brake	Hydr.Disc ø240mm (ABS)

Dimensions

Overall L*W*H	2030*775*1130mm
Wheel base	1420mm
Seat height	790mm
Ground clearance	140mm
Curb weight	191kg
Fuel capacity	14.3L

Available Colours:    

Homologation: 250: E-Mark
400: E5,EPA

QJMOTOR

SRK 250 RS (QJ250GS-29E)

SPORT RACING



Engine

Type	1-Cylinder, 4V DOHC, Liquid-Cooled
Bore*Stroke	72.0*61.2mm
Displacement	249cc
Max.Horsepower	20.5KW/9500RPM
MAX.Torque	22.5NM/7250RPM
Fuel system	EFI
Starting system	Electric
Clutch	Manual,multilate Wet Clutch
Transmission	6 Gears, Chain

Chassis

Front suspension	Telescopic Upside-Down
Rear suspension	Telescopic coil spring oil damped
Front tyre	110/70 R17
Rear tyre	140/60 R17
Front brake	Hydr.Disc ø300mm(ABS)
Rear brake	Hydr.Disc ø240mm(ABS)

Dimensions

Overall L*W*H	2010*770*1125mm
Wheel base	1360mm
Seat height	780mm
Ground clearance	135mm
Curb weight	162kg
Fuel capacity	12.5L

Available Colours:    

Homologation: E-Mark

QJMOTOR

SRK 250 RC (QJ250GS-16D)

SPORT RACING



Engine

Type	2-Cylinder, 8V DOHC, Water cooled
Bore*Stroke	62.0*41.3mm
Displacement	249cc
Max.Horsepower	27.0KW/13000RPM
MAX.Torque	23.0NM/10000RPM
Fuel system	EFI
Starting system	Electric
Clutch	Wet multi-plate
Transmission	6 Gears, Chain

Chassis

Front suspension	Telescopic Upside-Down
Rear suspension	Telescopic coil spring oil damped
Front tyre	110/70 R17
Rear tyre	150/60 R17
Front brake	Disc
Rear brake	Disc ø240mm

Dimensions

Overall L*W*H	2030*750*1150mm
Wheel base	1380mm
Seat height	780mm
Ground clearance	135mm
Curb weight	183kg
Fuel capacity	14.8L

Available Colours:   

Homologation: E5

QJMOTOR

SRK 25 R (QJ250GS-29F)

SPORT RACING



Engine

Type	1-Cylinder, 4V DOHC, Liquid-Cooled
Bore*Stroke	72.0*61.2mm
Displacement	249cc
Max.Horsepower	20.5KW/9500RPM
MAX.Torque	22.5NM/7250RPM
Fuel system	EFI
Starting system	Electric
Clutch	Manual, multilate Wet Clutch
Transmission	6 Gears, Chain

Chassis

Front suspension	Telescopic Upside-Down
Rear suspension	Telescopic coil spring oil damped
Front tyre	110/70 R17
Rear tyre	140/60 R17
Front brake	Hydr.Disc ø300mm(ABS)
Rear brake	Hydr.Disc ø240mm(ABS)

Dimensions

Overall L*W*H	2010*770*1125mm
Wheel base	1360mm
Seat height	780mm
Ground clearance	135mm
Curb weight	162kg
Fuel capacity	12.5L

Available Colours:    

Homologation: E-Mark, E5+

QJMOTOR

SRK 125 R (QJ125GS-29F)

SPORT RACING



Engine

Type	1-Cylinder,4V SOHC,Liquid-Cooled
Bore*Stroke	54.0*54.5mm
Displacement	125cc
Max.Horsepower	11.0KW/9500RPM
MAX.Torque	12.1NM/7000RPM
Fuel system	EFI
Starting system	Electric
Clutch	Wet multi-plate
Transmission	6 Gears,Chain

Chassis

Front suspension	Telescopic Upside-Down
Rear suspension	Telescopic coil spring oil damped
Front tyre	100/80-17
Rear tyre	130/70-17
Front brake	Disc ø260mm(ABS)
Rear brake	Disc ø240mm(ABS)

Dimensions

Overall L*W*H	2010*770*1130mm
Wheel base	1360mm
Seat height	785(765)mm
Ground clearance	140mm
Curb weight	153kg
Fuel capacity	12.5L

Available Colours:    

Homologation: E5,E5+

RJMOTOR

SRT Series



QJMOTOR

SRT 900 SX (QJ900-7E)

ADVENTURE



Engine

Type	2-Cylinder Inline, 8V DOHC, Liquid-Cooled
Bore*Stroke	92.0*68.0mm
Displacement	904cc
Max.Horsepower	70.0KW/9000RPM
MAX.Torque	90.0NM/6500RPM
Fuel system	EFI
Starting system	Electric
Clutch	Wet multi-plate
Transmission	6 Gears, Chain

Chassis

Front suspension	Telescopic Upside-Down
Rear suspension	Telescopic coil spring oil damped
Front tyre	110/80 R19
Rear tyre	150/70 R17
Front brake	Disc ø320mm
Rear brake	Disc ø260mm

Dimensions

Overall L*W*H	2250*950*1390mm
Wheel base	1540mm
Seat height	835mm
Ground clearance	210mm
Curb weight	264kg
Fuel capacity	24L

Available Colours:   

Homologation: E-Mark, E5+

QJMOTOR

SRT 900 S (QJ900-7E)

ADVENTURE



Engine

Type	2-Cylinder Inline, 8V DOHC, Liquid-Cooled
Bore*Stroke	92.0*68.0mm
Displacement	904cc
Max.Horsepower	70.0KW/9000RPM
MAX.Torque	90.0NM/6500RPM
Fuel system	EFI
Starting system	Electric
Clutch	Wet multi-plate
Transmission	6 Gears, Chain

Chassis

Front suspension	Telescopic Upside-Down
Rear suspension	Telescopic coil spring oil damped
Front tyre	120/70ZR17
Rear tyre	180/55ZR17
Front brake	Disc ø320mm
Rear brake	Disc ø260mm

Dimensions

Overall L*W*H	2250*950*1390mm
Wheel base	1540mm
Seat height	815mm
Ground clearance	210mm
Curb weight	257kg
Fuel capacity	24L

Available Colours:   

Homologation: E-Mark, E5+

QJMOTOR

SRT 800 SX (QJ800-7B)

ADVENTURE



Engine

Type	2-Cylinder Inline, 8V DOHC, Liquid-Cooled
Bore*Stroke	88.0*65.7mm
Displacement	799cc
Max.Horsepower	68.0KW/9000RPM (35.0KW/6500RPM)
MAX.Torque	77.0NM/8000RPM (58.0NM/5250RPM)
Fuel system	EFI
Starting system	Electric
Clutch	Wet multi-plate
Transmission	6 Gears, Chain

Chassis

Front suspension	Telescopic Upside-Down
Rear suspension	Telescopic coil spring oil damped
Front tyre	110/80-19
Rear tyre	150/70-17
Front brake	Disc ø320mm(double)(ABS)
Rear brake	Disc ø260mm(ABS)

Dimensions

Overall L*W*H	2260*950*1405mm
Wheel base	1540mm
Seat height	835mm
Ground clearance	180mm
Curb weight	263kg
Fuel capacity	24L

Available Colours:  

Homologation: E-Mark, E5, E5+

QJMOTOR

SRT 800 S (QJ800-7B)

ADVENTURE



Engine

Type	2-Cylinder Inline, 8V DOHC, Liquid-Cooled
Bore*Stroke	88.0*65.7mm
Displacement	799cc
Max.Horsepower	68.0KW/9000RPM (35.0KW/6500RPM)
MAX.Torque	77.0NM/8000RPM (58.0NM/5250RPM)
Fuel system	EFI
Starting system	Electric
Clutch	Wet multi-plate
Transmission	6 Gears, Chain

Chassis

Front suspension	Telescopic Upside-Down
Rear suspension	Telescopic coil spring oil damped
Front tyre	120/70ZR17
Rear tyre	180/55ZR17
Front brake	Disc ø320mm(double)(ABS)
Rear brake	Disc ø260mm(ABS)

Dimensions

Overall L*W*H	2240*950*1390mm
Wheel base	1540mm
Seat height	810mm
Ground clearance	180mm
Curb weight	257kg
Fuel capacity	24L

Available Colours:  

Homologation: E-Mark, E5, E5+

QJMOTOR

SRT 700 X (QJ700-5J)

ADVENTURE



Engine

Type	2-Cylinder Inline, 8V DOHC, Liquid-Cooled
Bore*Stroke	83.0*64.5mm
Displacement	698cc
Max.Horsepower	54.0KW/8000RPM (35.0KW/6500RPM)
MAX.Torque	67.0NM/6000RPM (58.0NM/5250RPM)
Fuel system	EFI
Starting system	Electric
Clutch	Wet multi-plate
Transmission	6 Gears, Chain

Chassis

Front suspension	Telescopic Upside-Down
Rear suspension	Telescopic coil spring oil damped
Front tyre	110/80 R19 (Spoke)
Rear tyre	150/70 R17 (Spoke)
Front brake	Disc ø320mm (double)(ABS)
Rear brake	Disc ø260mm (ABS)

Dimensions

Overall L*W*H	2220*925*1480
Wheel base	1505mm
Seat height	825mm
Ground clearance	190mm
Curb weight	240kg
Fuel capacity	19.5L

Available Colours:    

Homologation: E-Mark,E5,E5+

QJMOTOR

SRT 700 (QJ700-5J)

ADVENTURE



Engine

Type	2-Cylinder Inline, 8V DOHC, Liquid-Cooled
Bore*Stroke	83.0*64.5mm
Displacement	698cc
Max.Horsepower	54.0KW/8000RPM (35.0KW/6500RPM)
MAX.Torque	67.0NM/6000RPM (58.0NM/5250RPM)
Fuel system	EFI
Starting system	Electric
Clutch	Wet multi-plate
Transmission	6 Gears, Chain

Chassis

Front suspension	Telescopic Upside-Down
Rear suspension	Telescopic coil spring oil damped
Front tyre	120/70 ZR17
Rear tyre	160/60 ZR17
Front brake	Disc ø320mm (double)(ABS)
Rear brake	Disc ø260mm (ABS)

Dimensions

Overall L*W*H	2200*925*1450mm
Wheel base	1505mm
Seat height	795mm
Ground clearance	190mm
Curb weight	235kg
Fuel capacity	19.5L

Available Colours:    

Homologation: E-Mark,E5,E5+

QJMOTOR

SRT 700 SX (QJ700-5S)

ADVENTURE



Engine

Type	2-Cylinder Inline, DOHC, Liquid-Cooled
Bore*Stroke	83.0*64.5mm
Displacement	698cc
Max.Horsepower	51.5KW/8000RPM
MAX.Torque	70.0NM/6000RPM
Fuel system	EFI
Starting system	Electric
Clutch	Wet multi-plate
Transmission	6 Gears, Chain

Chassis

Front suspension	Telescopic Upside Down
Rear suspension	Telescopic coil spring oil damped
Front tyre	110/80 R19
Rear tyre	150/70 R17
Front brake	Disc ø320mm
Rear brake	Disc ø260mm

Dimensions

Overall L*W*H	2225*925*1420
Wheel base	1510mm
Seat height	825mm
Ground clearance	210mm
Curb weight	243kg
Fuel capacity	19.5L

Available Colours:    

Homologation: E5, E5+

QJMOTOR

SRT 700 S (QJ700-5S)

ADVENTURE



Engine

Type	2-Cylinder Inline, DOHC, Liquid-Cooled
Bore*Stroke	83.0*64.5mm
Displacement	698cc
Max.Horsepower	51.5KW/8000RPM
MAX.Torque	70.0NM/6000RPM
Fuel system	EFI
Starting system	Electric
Clutch	Wet multi-plate
Transmission	6 Gears, Chain

Chassis

Front suspension	Telescopic Upside-Down
Rear suspension	Telescopic coil spring oil damped
Front tyre	120/70 ZR17
Rear tyre	160/60 ZR17
Front brake	Disc ø320mm
Rear brake	Disc ø260mm

Dimensions

Overall L*W*H	2200*925*1390mm
Wheel base	1510mm
Seat height	795mm
Ground clearance	190mm
Curb weight	238kg
Fuel capacity	19.5L

Available Colours:    

Homologation: E5, E5+

QJMOTOR

SVT 650 X (QJ650-16A)

ADVENTURE



Engine

Type	2-Cylinder V,8V DOHC,Liquid-Cooled
Bore*Stroke	81.0*62.6mm
Displacement	645cc
Max.Horsepower	56.0KW/9000RPM
MAX.Torque	65.0NM/8000RPM
Fuel system	EFI
Starting system	Electric
Clutch	Wet multi-plate
Transmission	Chain

Chassis

Front suspension	Telescopic Upside-Down
Rear suspension	Telescopic coil spring oil damped
Front tyre	110/80 R19
Rear tyre	150/70 R17
Front brake	Hydr.Disc ø320mm (double)(ABS)
Rear brake	Hydr.Disc ø260mm (ABS)

Dimensions

Overall L*W*H	2270*950*1405mm
Wheel base	1505mm
Seat height	795mm
Ground clearance	170mm
Curb weight	236kg
Fuel capacity	20.0L

Available Colours:   

Homologation: E-Mark,E5,E5+

QJMOTOR

SVT 650 (QJ650-16A)

ADVENTURE



Engine

Type	2-Cylinder V,8V DOHC,Liquid-Cooled
Bore*Stroke	81.0*62.6mm
Displacement	645cc
Max.Horsepower	56.0KW/9000RPM
MAX.Torque	65.0NM/8000RPM
Fuel system	EFI
Starting system	Electric
Clutch	Wet multi-plate
Transmission	Chain

Chassis

Front suspension	Telescopic Upside-Down
Rear suspension	Telescopic coil spring oil damped
Front tyre	110/80 R19
Rear tyre	150/70 R17
Front brake	Hydr.Disc ø320mm (double)(ABS)
Rear brake	Hydr.Disc ø260mm (ABS)

Dimensions

Overall L*W*H	2270*950*1405mm
Wheel base	1505mm
Seat height	795mm
Ground clearance	170mm
Curb weight	236kg
Fuel capacity	20.0L

Available Colours:   

Homologation: E-Mark,E5,E5+

QJMOTOR

SRT 600 SX (QJ500-7C)

ADVENTURE



Engine

Type	2-Cylinder Inline, 8V DOHC, Liquid-Cooled
Bore*Stroke	70.5*71.0mm
Displacement	554cc
Max.Horsepower	41.2KW/8250RPM
MAX.Torque	54.0NM/5500RPM
Fuel system	EFI
Starting system	Electric
Clutch	Wet multi-plate
Transmission	6 Gears, Chain

Chassis

Front suspension	Telescopic Upside-Down
Rear suspension	Telescopic coil spring oil damped
Front tyre	110/80 R19 M/C (Spoke)
Rear tyre	150/70 R17 M/C (Spoke)
Front brake	Disc ø320mm(double)
Rear brake	Disc ø260mm

Dimensions

Overall L*W*H	2200*900*1380mm
Wheel base	1500mm
Seat height	845mm
Ground clearance	190mm
Curb weight	220kg
Fuel capacity	20.5L

Available Colours:   

Homologation: E5, E5+

QJMOTOR

SRT 600 S (QJ500-7C)

ADVENTURE



Engine

Type	2-Cylinder Inline, 8V DOHC, Liquid-Cooled
Bore*Stroke	70.5*71.0mm
Displacement	554cc
Max.Horsepower	41.2KW/8250RPM
MAX.Torque	54.0NM/5500RPM
Fuel system	EFI
Starting system	Electric
Clutch	Wet multi-plate
Transmission	6 Gears, Chain

Chassis

Front suspension	Telescopic Upside-Down
Rear suspension	Telescopic coil spring oil damped
Front tyre	120/70 ZR17 M/C (Alloy)
Rear tyre	160/60 ZR17 M/C (Alloy)
Front brake	Disc ø320mm(double)
Rear brake	Disc ø260mm

Dimensions

Overall L*W*H	2190*896*1378mm
Wheel base	1480mm
Seat height	830mm
Ground clearance	190mm
Curb weight	215kg
Fuel capacity	20.2L

Available Colours:   

Homologation: E5, E5+

QJMOTOR

SRT 600 X (QJ500-5R)

ADVENTURE



Engine

Type	2-Cylinder Inline, 8V DOHC, Liquid-Cooled
Bore*Stroke	70.5*71.0mm
Displacement	554cc
Max.Horsepower	41.2KW/8250RPM
MAX.Torque	54.0NM/5500RPM
Fuel system	EFI
Starting system	Electric
Clutch	Wet multi-plate
Transmission	6 Gears, Chain

Chassis

Front suspension	Telescopic Upside-Down
Rear suspension	Telescopic coil spring oil damped
Front tyre	110/80 R19 (Spoke)
Rear tyre	150/70 R17 (Spoke)
Front brake	Hydr.Disc ø320mm (double)(ABS)
Rear brake	Hydr.Disc ø260mm (ABS)

Dimensions

Overall L*W*H	2220*925*1480mm
Wheel base	1505mm
Seat height	825mm
Ground clearance	220mm
Curb weight	235kg
Fuel capacity	19.5L

Available Colours:   

Homologation: E-Mark, E5, E5+

QJMOTOR

SRT 600 (QJ500-5P)

ADVENTURE



Engine

Type	2-Cylinder Inline, 8V DOHC, Liquid-Cooled
Bore*Stroke	70.5*71.0mm
Displacement	554cc
Max.Horsepower	41.2KW/8250RPM
MAX.Torque	54.0NM/5500RPM
Fuel system	EFI
Starting system	Electric
Clutch	Wet multi-plate
Transmission	6 Gears, Chain

Chassis

Front suspension	Telescopic Upside-Down
Rear suspension	Telescopic coil spring oil damped
Front tyre	120/70 ZR17 M/C (Alloy)
Rear tyre	160/60 ZR17 M/C (Alloy)
Front brake	Hydr.Disc ø320mm (double)(ABS)
Rear brake	Hydr.Disc ø260mm (ABS)

Dimensions

Overall L*W*H	2200*925*1450mm
Wheel base	1505mm
Seat height	795mm
Ground clearance	190mm
Curb weight	235kg
Fuel capacity	19.5L

Available Colours:   

Homologation: E-Mark, E5, E5+

QJMOTOR

COV 125 X (QJ125Y-17E)

ADVENTURE



Engine

Type	1-Cylinder,4V SOHC,Liquid-Cooled
Bore*Stroke	54.0*54.5mm
Displacement	124.8cc
Max.Horsepower	11.0KW/9500RPM
MAX.Torque	12.5NM/7500RPM
Fuel system	EFI
Starting system	Electric
Clutch	Wet multi-plate
Transmission	6 Gears,Chain

Chassis

Front suspension	Upside down telescopic forks
Rear suspension	Telescopic coil spring oil damped
Front tyre	100/80-17
Rear tyre	130/70-17
Front brake	Disc ø320mm
Rear brake	Disc ø220mm

Dimensions

Overall L*W*H	2025*800*1187mm
Wheel base	1425mm
Seat height	885mm
Ground clearance	275mm
Curb weight	115kg
Fuel capacity	7.5±0.3L

Available Colours:   

Homologation: /

RJMOTOR

SRV Series



QJMOTOR

SRV 700 (QJ700-11A)

STREET CRUISER



Engine

Type	2-Cylinder ,8V DOHC,Liquid-Cooled
Bore*Stroke	83.0*64.0mm
Displacement	698cc
Max.Horsepower	54.0KW/8000RPM
MAX.Torque	67.0NM/6000RPM
Fuel system	EFI
Starting system	Electric
Clutch	Wet multi-plate
Transmission	6 Gears,Chain or Belt

Chassis

Front suspension	Telescopic Upside-Down
Rear suspension	Telescopic coil spring oil damped
Front tyre	130/90 ZR16
Rear tyre	150/80 ZR16
Front brake	Disc ø300mm(double)(ABS)
Rear brake	Disc ø260mm(ABS)

Dimensions

Overall L*W*H	2230*830*1160mm
Wheel base	1580mm
Seat height	720mm
Ground clearance	160mm
Curb weight	208kg
Fuel capacity	16L

Available Colours:   

Homologation: E-Mark,E5

QJMOTOR

SRV 600 ST (QJ500-11C/D)

// STREET CRUISER



Engine

Type	2-Cylinder Inline, 8V DOHC, Liquid-Cooled
Bore*Stroke	70.5*71.0mm
Displacement	554cc
Max.Horsepower	41.2KW/8250RPM
MAX.Torque	54.0NM/5500RPM
Fuel system	EFI
Starting system	Electric
Clutch	Wet multi-plate
Transmission	6 Gears, Chain

Chassis

Front suspension	Telescopic forks
Rear suspension	Telescopic coil spring oil damped
Front tyre	120/70 R18 or 130/90-16
Rear tyre	160/60 R17 or 150/80-16
Front brake	Hydr.Disc ø300mm(ABS)
Rear brake	Hydr.Disc ø250mm(ABS)

Dimensions

Overall L*W*H	2230*865*1130mm
Wheel base	1580mm
Seat height	735mm
Ground clearance	160mm
Curb weight	212kg
Fuel capacity	16L

Available Colours:    

Homologation: E-Mark, E5, E5+

QJMOTOR

SRV 600 V (QJ600-12B)

// STREET CRUISER



Engine

Type	4-Cylinder,DOHC,Liquid-Cooled
Bore*Stroke	61.0*48.0mm
Displacement	561cc
Max.Horsepower	50.0KW/10500RPM
MAX.Torque	54.0NM/8000RPM
Fuel system	EFI
Starting system	Electric
Clutch	Wet multi-plate
Transmission	6 Gears,Belt

Chassis

Front suspension	Telescopic Upside-Down
Rear suspension	Telescopic coil spring oil damped
Front tyre	130/90-16
Rear tyre	180/65-16
Front brake	Disc ø300mm(double)
Rear brake	Disc ø260mm

Dimensions

Overall L*W*H	2280*830*1115mm
Wheel base	1580mm
Seat height	720mm
Ground clearance	140mm
Curb weight	219kg
Fuel capacity	16.5L

Available Colours:   

Homologation: E-Mark,E5,E5+

QJMOTOR

SRV 600 V2 (QJ600-12L)

// STREET CRUISER



Engine

Type	2-Cylinder V, 8V DOHC, Liquid-Cooled
Bore*Stroke	70.5*70.5mm
Displacement	550.4cc
Max.Horsepower	37.0KW/8000RPM
MAX.Torque	53.0NM/6500RPM
Fuel system	EFI
Starting system	Electric
Clutch	Wet multi-plate
Transmission	6 Gears,Belt

Chassis

Front suspension	Upside down telescopic forks
Rear suspension	Side mounted shock absorber
Front tyre	130/90-16
Rear tyre	180/65-16
Front brake	Disc ø320mm
Rear brake	Disc ø360mm

Dimensions

Overall L*W*H	2190*830*1150mm
Wheel base	1555mm
Seat height	705mm
Ground clearance	120mm
Curb weight	205kg
Fuel capacity	16L

Available Colours:  

Homologation: /

QJMOTOR

SRV 400 VS (QJ400-12K)

// STREET CRUISER



Engine

Type	2-Cylinder V, 8V DOHC, Liquid-Cooled
Bore*Stroke	60.0*68.0mm
Displacement	385cc
Max.Horsepower	26.0KW/8000RPM
MAX.Torque	36.0NM/4500RPM
Fuel system	EFI
Starting system	Electric
Clutch	Wet multi-plate
Transmission	6 Gears,Belt

Chassis

Front suspension	Upside down telescopic forks
Rear suspension	Side mounted shock absorber
Front tyre	130/90-16
Rear tyre	150/80-16
Front brake	Disc
Rear brake	Disc

Dimensions

Overall L*W*H	2220*830*1100mm
Wheel base	1520mm
Seat height	734mm
Ground clearance	160mm
Curb weight	173kg
Fuel capacity	16L

Available Colours:  

Homologation: E5+

QJMOTOR

SRV 350 VS (QJ350-12E)

// STREET CRUISER



Engine

Type	2-Cylinder V,SOHC,Liquid-Cooled
Bore*Stroke	58.0*65.0mm
Displacement	343cc
Max.Horsepower	23.5KW/8500RPM
MAX.Torque	31.0NM/5000RPM
Fuel system	EFI
Starting system	Electric
Clutch	Wet multi-plate
Transmission	6 Gears,Belt

Chassis

Front suspension	Telescopic Upside-Down
Rear suspension	Telescopic coil spring oil damped
Front tyre	130/90-16
Rear tyre	150/80-16
Front brake	Disc ø300mm(ABS)
Rear brake	Disc ø240mm(ABS)

Dimensions

Overall L*W*H	2210*830*1100mm
Wheel base	1520mm
Seat height	720mm
Ground clearance	170mm
Curb weight	182kg
Fuel capacity	16L

Available Colours:   

Homologation: 350: E5
250: E-Mark

QJMOTOR

SRV 300 A (QJ300-12N)

STREET CRUISER



Engine

Type	2-Cylinder V, 8V SOHC, Liquid-Cooled
Bore*Stroke	58.0*56.0mm
Displacement	296cc
Max.Horsepower	22.6KW/9000RPM
MAX.Torque	26.0NM/5000RPM
Fuel system	EFI
Starting system	Electric
Clutch	Wet multi-plate
Transmission	AMT,Belt

Chassis

Front suspension	Upside down telescopic forks
Rear suspension	Telescopic coil spring oil damped
Front tyre	120/80-16
Rear tyre	150/80-15
Front brake	Disc ø280mm
Rear brake	Disc ø240mm

Available Colours:  

Dimensions

Overall L*W*H	2110*850*1100mm
Wheel base	1400mm
Seat height	700mm
Ground clearance	160mm
Curb weight	164kg
Fuel capacity	13.5L

Homologation: /

QJMOTOR

SRV 300 (QJ300-12A)

STREET CRUISER



Engine

Type	2-Cylinder V-Twin, 8V SOHC, Liquid-Cooled
Bore*Stroke	58.0*56.0mm
Displacement	296cc
Max.Horsepower	22.6KW/9000RPM
MAX.Torque	26.0NM/5000RPM
Fuel system	EFI
Starting system	Electric
Clutch	Manual,multilate Wet Clutch
Transmission	6 Gears,Chain or Belt

Chassis

Front suspension	Telescopic Upside-Down
Rear suspension	Telescopic coil spring oil damped
Front tyre	120/80-16
Rear tyre	150/80-15
Front brake	Hydr.Disc ø280mm(ABS)
Rear brake	Hydr.Disc ø240mm(ABS)

Dimensions

Overall L*W*H	2110*850*1100mm
Wheel base	1400mm
Seat height	700mm
Ground clearance	160mm
Curb weight	164kg
Fuel capacity	13.5L

Available Colours:    

Homologation: 300: E5,E5+
250: E-Mark

QJMOTOR

SRV 250 (QJ250-12A)

// STREET CRUISER



Engine

Type	2-Cylinder V,4V SOHC,Liquid-Cooled
Bore*Stroke	58.0*47.2mm
Displacement	249cc
Max.Horsepower	20.5KW/9000RPM
MAX.Torque	23.0NM/8000RPM
Fuel system	EFI
Starting system	Electric
Clutch	Wet multi-plate
Transmission	6 Gears,Chain

Chassis

Front suspension	Telescopic Upside-Down
Rear suspension	Telescopic coil spring oil damped
Front tyre	120/80-16
Rear tyre	150/80-15
Front brake	Disc ø280mm(ABS)
Rear brake	Disc ø240mm(ABS)

Dimensions

Overall L*W*H	2110*850*1100mm
Wheel base	1400mm
Seat height	700mm
Ground clearance	160mm
Curb weight	167kg
Fuel capacity	13.5L

Available Colours:   

Homologation: E-Mark

QJMOTOR

SRV 200 (QJ200-2L)

STREET CRUISER



Engine

Type	1-Cylinder,OHV,2V
Bore*Stroke	63.5*62.2mm
Displacement	197cc
Max.Horsepower	9.5KW/7500RPM
MAX.Torque	13.9NM/6000RPM
Fuel system	Carburetor or EFI
Starting system	Electric & Kick
Clutch	Wet Clutch
Transmission	5 Gears,Chain

Chassis

Front suspension	Telescopic forks
Rear suspension	Telescopic coil spring oil damped
Front tyre	90/90-17
Rear tyre	130/90-15
Front brake	Disc ø280mm
Rear brake	Disc ø240mm

Dimensions

Overall L*W*H	2120*825*1050mm
Wheel base	1445mm
Seat height	720mm
Ground clearance	140mm
Curb weight	152kg
Fuel capacity	14.7L

Available Colours:     

Homologation: E-Mark

QJMOTOR

SRV 125 (QJ125-2K)

// STREET CRUISER



Engine

Type	1-Cylinder, 4V, SOHC, Liquid-Cooled
Bore*Stroke	54.0*54.5mm
Displacement	125cc
Max.Horsepower	11.0KW/9500RPM
MAX.Torque	12.1NM/7000RPM
Fuel system	EFI
Starting system	Electric
Clutch	Wet multi-plate
Transmission	6 Gears, Chain

Chassis

Front suspension	Telescopic forks
Rear suspension	Telescopic coil spring oil damped
Front tyre	90/90-17
Rear tyre	140/90-15
Front brake	Disc ø280mm (ABS)
Rear brake	Disc ø240mm (ABS)

Dimensions

Overall L*W*H	2140*780*1050mm
Wheel base	1440mm
Seat height	720mm
Ground clearance	140mm
Curb weight	150kg
Fuel capacity	14.7L

Available Colours:    

Homologation: 150: E-Mark
125: E5,E5+

QJMOTOR

SRV 12 (QJ125-12H)

// STREET CRUISER



Engine

Type	2-Cylinder, 4V SOHC, Liquid-Cooled
Bore*Stroke	42.0*45.0mm
Displacement	125cc
Max.Horsepower	10.3KW/10000RPM
MAX.Torque	10.2NM/9250RPM
Fuel system	EFI
Starting system	Electric
Clutch	Wet multi-plate
Transmission	6 Gears, Chain

Chassis

Front suspension	Upside down telescopic forks
Rear suspension	Telescopic coil spring oil damped
Front tyre	120/80-16
Rear tyre	150/80-15
Front brake	Disc ø240mm
Rear brake	Disc ø280mm

Dimensions

Overall L*W*H	2110*840*1080mm
Wheel base	1400mm
Seat height	700mm
Ground clearance	160mm
Curb weight	163kg
Fuel capacity	13.5L

Available Colours:  

Homologation: E5+

QJMOTOR

SRV 600 (QJ500-19)

STREET CRUISER



Engine

Type	2-Cylinder Inline, 8V DOHC, Liquid-Cooled
Bore*Stroke	70.5*71.0mm
Displacement	554cc
Max.Horsepower	41.2KW/8250RPM
MAX.Torque	54.0NM/5500RPM
Fuel system	EFI
Starting system	Electric
Clutch	Wet multi-plate
Transmission	6 Gears, Chain

Chassis

Front suspension	Telescopic Upside-Down
Rear suspension	Telescopic coil spring oil damped
Front tyre	120/70 ZR17
Rear tyre	160/60 ZR17
Front brake	Hydr.Disc ø320mm (double)(ABS)
Rear brake	Hydr.Disc ø260mm (ABS)

Dimensions

Overall L*W*H	2100*880*1160mm
Wheel base	1440mm
Seat height	785mm
Ground clearance	150mm
Curb weight	206kg
Fuel capacity	16L

Available Colours:   

Homologation: E-Mark,E5,E5+,EPA

QJMOTOR

SRC 400 (QJ400-8C)

COMMUTE



Engine

Type	1-Cylinder, 2V SOHC, Air-Cooled
Bore*Stroke	72.7*90.0mm
Displacement	374cc
Max.Horsepower	15.5KW/5500RPM
MAX.Torque	29.0NM/4500RPM
Fuel system	EFI
Starting system	Electric
Clutch	Manual, multilate Wet Clutch
Transmission	5 Gears, Chain

Chassis

Front suspension	Telescopic forks
Rear suspension	Telescopic coil spring oil damped
Front tyre	100/90-19
Rear tyre	130/80-18
Front brake	Hydr.Disc ø300mm (ABS)
Rear brake	Hydr.Disc ø240mm (ABS)

Dimensions

Overall L*W*H	2170*820*1120mm
Wheel base	1440mm
Seat height	800mm
Ground clearance	155mm
Curb weight	205kg
Fuel capacity	15L

Available Colours:   

Homologation: E5, E5+

QJMOTOR

SRV 249 (QJ250-19)

STREET CRUISER



Engine

Type	2-Cylinder Inline, 8V DOHC, Liquid-Cooled
Bore*Stroke	61.0*42.7mm
Displacement	249.6cc
Max.Horsepower	25.7KW/12500RPM
MAX.Torque	21.2NM/9000RPM
Fuel system	EFI
Starting system	Electric
Clutch	Wet multi-plate
Transmission	6 Gears, Chain

Chassis

Front suspension	Telescopic Upside-Down
Rear suspension	Telescopic coil spring oil damped
Front tyre	110/70 R17
Rear tyre	150/60 R17
Front brake	Disc ø300mm(ABS)
Rear brake	Disc ø240mm(ABS)

Dimensions

Overall L*W*H	2100*865*1160mm
Wheel base	1440mm
Seat height	785mm
Ground clearance	160mm
Curb weight	195kg
Fuel capacity	16L

Available Colours:   

Homologation: E-Mark

QJMOTOR

SRC 250 (QJ250-9)

STREET CRUISER



Engine

Type	2-Cylinder Inline, 4V SOHC, Liquid-Cooled
Bore*Stroke	55.0*52.4mm
Displacement	249cc
Max.Horsepower	13.0KW/8000RPM
MAX.Torque	17.0NM/6000RPM
Fuel system	EFI
Starting system	Electric
Clutch	Manual, multilate Wet Clutch
Transmission	5Gears, Chain

Chassis

Front suspension	Telescopic forks
Rear suspension	Telescopic coil spring oil damped
Front tyre	90/90-18
Rear tyre	130/90-15
Front brake	Hydr.Disc ø280mm (ABS)
Rear brake	Hydr.Disc ø240mm (ABS)

Dimensions

Overall L*W*H	2070*810*1100mm
Wheel base	1370mm
Seat height	780mm
Ground clearance	160mm
Curb weight	163kg
Fuel capacity	14L

Available Colours:   

Homologation: E5

QJMOTOR

Scooter Series



QJMOTOR

FORT 400/4.0 (QJ350T-2D)

/ SCOOTER



Engine

Type	SOHC, Liquid-Cooled
Bore*Stroke	80.0*69.6mm
Displacement	350cc
Max.Horsepower	25.2KW/7500RPM
MAX.Torque	35.2NM/6000RPM
Fuel system	EFI
Starting system	Electric
Clutch	Automatic CVT
Transmission	Belt

Chassis

Front suspension	Telescopic forks
Rear suspension	DoubleTelescopic coil spring oil damped
Front tyre	120/70-15
Rear tyre	150/70-14
Front brake	Hydr.Disc
Rear brake	Hydr.Disc

Dimensions

Overall L*W*H	2320*780*1390mm
Wheel base	1565mm
Seat height	775mm
Ground clearance	150mm
Curb weight	213kg
Fuel capacity	14L

Available Colours:   

Homologation: E-mark,E5,E5+

QJMOTOR

FORT 250 (QJ250T-9A)

/ SCOOTER



Engine

Type	1-Cylinder,SOHC,Liquid-Cooled
Bore*Stroke	70*64.9mm
Displacement	249.7cc
Max.Horsepower	17.0KW/8000RPM
MAX.Torque	24.0NM/6500RPM
Fuel system	EFI
Starting system	Electric
Clutch	Wet multi-plate Automatic CVT
Transmission	Belt

Chassis

Front suspension	Positive shock absorption
Rear suspension	Centre shock absorption
Front tyre	120/70-13
Rear tyre	150/70-13
Front brake	Disc ø260mm
Rear brake	Disc ø240mm

Available Colours: ☐ ☐

Dimensions

Overall L*W*H	2180*805*1280mm
Wheel base	1513mm
Seat height	765mm
Ground clearance	145mm
Curb weight	188kg
Fuel capacity	10L

Homologation: E5

QJMOTOR

FORT 250 (QJ250T-9D)

SCOOTER



Engine

Type	1-Cylinder,SOHC,Liquid-Cooled
Bore*Stroke	70.0*64.9mm
Displacement	249.7cc
Max.Horsepower	17.0KW/8000RPM
MAX.Torque	24.0NM/6500RPM
Fuel system	EFI
Starting system	Electric
Clutch	Automatic CVT
Transmission	Belt

Chassis

Front suspension	Telescopic forks
Rear suspension	Telescopic coil spring oil damped
Front tyre	120/70-13
Rear tyre	150/70-13
Front brake	Disc ø260mm
Rear brake	Disc ø240mm

Available Colours:

Dimensions

Overall L*W*H	2180*805*1280mm
Wheel base	1513mm
Seat height	765mm
Ground clearance	145mm
Curb weight	190kg
Fuel capacity	13±0.5L

Homologation: /

QJMOTOR

MTX 250 (QJ250T-23N)

SCOOTER



Engine

Type	1-Cylinder, 4V SOHC, Liquid-Cooled
Bore*Stroke	70.0*64.8mm
Displacement	249cc
Max.Horsepower	19.0KW/8000RPM
MAX.Torque	24.5NM/6500RPM
Fuel system	EFI
Starting system	Electric
Clutch	Automatic CVT
Transmission	Belt

Chassis

Front suspension	Telescopic forks
Rear suspension	Telescopic coil spring oil damped
Front tyre	110/80-14
Rear tyre	130/70-13
Front brake	Disc ø240mm
Rear brake	Disc ø220mm

Dimensions

Overall L*W*H	1945*770*1230mm
Wheel base	1360mm
Seat height	755mm
Ground clearance	120mm
Curb weight	158kg
Fuel capacity	12.5L

Available Colours:   

Homologation: E5+

QJMOTOR

MTX 200 (QJ175T-23H)

/ SCOOTER



Engine

Type	1-Cylinder, 4V SOHC, Liquid-Cooled
Bore*Stroke	60.0*61.8mm
Displacement	175cc
Max.Horsepower	13.5KW/8000RPM
MAX.Torque	15.0NM/6500RPM
Fuel system	EFI
Starting system	Electric
Clutch	Automatic CVT
Transmission	Belt

Chassis

Front suspension	Telescopic forks
Rear suspension	Telescopic coil spring oil damped
Front tyre	110/80-14
Rear tyre	130/70-13
Front brake	Hydr.Disc ø240mm (ABS)
Rear brake	Hydr.Disc ø220mm (ABS)

Dimensions

Overall L*W*H	1945*755*1230mm
Wheel base	1325mm
Seat height	780mm
Ground clearance	140mm
Curb weight	133kg
Fuel capacity	8L

Available Colours:    

Homologation: E-Mark,E5+

QJMOTOR

ATR 200 (QJ175T-23F)

SCOOTER



Engine

Type	1-Cylinder, 4V SOHC, Liquid-Cooled
Bore*Stroke	60.0*61.8mm
Displacement	175cc
Max.Horsepower	13.5KW/8000RPM
MAX.Torque	15.0NM/6500RPM
Fuel system	EFI
Starting system	Electric
Clutch	Automatic CVT
Transmission	Belt

Chassis

Front suspension	Telescopic forks
Rear suspension	Telescopic coil spring oil damped
Front tyre	110/80-14
Rear tyre	130/70-13
Front brake	Hydr.Disc ø240mm(ABS)
Rear brake	Hydr.Disc ø220mm(ABS)

Dimensions

Overall L*W*H	1945*755*1230mm
Wheel base	1325mm
Seat height	780mm
Ground clearance	165mm
Curb weight	133kg
Fuel capacity	8L

Available Colours:    

Homologation: E-Mark,E5+

QJMOTOR

AX 200 S (QJ175T-23P)

SCOOTER



Engine

Type	1-Cylinder, 4V SOHC, Liquid-Cooled
Bore*Stroke	60.0*61.8mm
Displacement	175cc
Max.Horsepower	13.5KW/8500RPM
MAX.Torque	15.0NM/6500RPM
Fuel system	EFI
Starting system	Electric
Clutch	Automatic CVT
Transmission	Belt

Chassis

Front suspension	Telescopic forks
Rear suspension	Telescopic coil spring oil damped
Front tyre	100/80-14
Rear tyre	120/70-14
Front brake	Disc ø230mm
Rear brake	Disc ø220mm

Dimensions

Overall L*W*H	1965*700*1130mm
Wheel base	1360mm
Seat height	790mm
Ground clearance	145mm
Curb weight	127kg
Fuel capacity	10L

Available Colours:   

Homologation: E-Mark,E5+

QJMOTOR

SQ 20 (QJ175T-30E)

SCOOTER



Engine

Type	1-Cylinder, SOHC, Liquid-Cooled
Bore*Stroke	60.0*61.8mm
Displacement	175cc
Max.Horsepower	13.5KW/8500RPM
MAX.Torque	15.0NM/6500RPM
Fuel system	EFI
Starting system	Electric
Clutch	Automatic CVT
Transmission	Belt

Chassis

Front suspension	Telescopic forks
Rear suspension	Telescopic coil spring oil damped
Front tyre	100/80-16
Rear tyre	120/80-16
Front brake	Disc ø240mm
Rear brake	Disc ø240mm

Dimensions

Overall L*W*H	2100*735*1125mm
Wheel base	1350mm
Seat height	810mm
Ground clearance	146mm
Curb weight	136kg
Fuel capacity	7.8L

Available Colours:   

Homologation: E5+

QJMOTOR

RK0 150 W (QJ150T-6W)

SCOOTER



Engine

Type	1-Cylinder,SOHC,Liquid-Cooled
Bore*Stroke	57.3*57.9mm
Displacement	149cc
Max.Horsepower	12.2KW/8500RPM
MAX.Torque	14.8NM/6500RPM
Fuel system	EFI
Starting system	Electric
Clutch	Automatic CVT
Transmission	Belt

Chassis

Front suspension	Telescopic forks
Rear suspension	Telescopic coil spring oil damped
Front tyre	90/90-12
Rear tyre	100/80-12
Front brake	Disc ø190mm
Rear brake	Disc ø225mm

Dimensions

Overall L*W*H	2005*685*1170mm
Wheel base	1345mm
Seat height	770mm
Ground clearance	120mm
Curb weight	128kg
Fuel capacity	7L

Available Colours:   

Homologation: /

QJMOTOR

RK0 150 Y (QJ150T-6Y)

SCOOTER



Engine

Type	1-Cylinder,SOHC,Air-cooled
Bore*Stroke	57.3*57.9mm
Displacement	149cc
Max.Horsepower	9.0KW/8000RPM
MAX.Torque	12.2NM/6000RPM
Fuel system	EFI
Starting system	Electric
Clutch	Automatic CVT
Transmission	Belt

Chassis

Front suspension	Telescopic forks
Rear suspension	Telescopic coil spring oil damped
Front tyre	90/90-12
Rear tyre	100/80-12
Front brake	Disc ø190mm
Rear brake	Disc ø190mm

Dimensions

Overall L*W*H	2005*685*1170mm
Wheel base	1345mm
Seat height	770mm
Ground clearance	120mm
Curb weight	118kg
Fuel capacity	7L

Available Colours:   

Homologation: /

QJMOTOR

LTR 125 K (QJ125T-27K)

SCOOTER



Engine

Type	1-Cylinder, SOHC, Liquid-Cooled
Bore*Stroke	52.4*57.9mm
Displacement	124.9cc
Max.Horsepower	10.8KW/8750RPM
MAX.Torque	12.0NM/8250RPM
Fuel system	EFI
Starting system	Electric
Clutch	Automatic CVT
Transmission	Belt

Chassis

Front suspension	Telescopic forks
Rear suspension	Telescopic coil spring oil damped
Front tyre	90/90-12
Rear tyre	110/90-12
Front brake	Disc ø220mm
Rear brake	Disc ø225mm

Dimensions

Overall L*W*H	1900*710*1160mm
Wheel base	1300mm
Seat height	770mm
Ground clearance	140mm
Curb weight	118kg
Fuel capacity	8L

Available Colours:  

Homologation: E5+

QJMOTOR

RK0 125 W (QJ125T-6W)

SCOOTER



Engine

Type	1-Cylinder,SOHC,Liquid-Cooled
Bore*Stroke	52.5*57.9mm
Displacement	124.9cc
Max.Horsepower	10.8KW/8750RPM
MAX.Torque	12.0NM/8250RPM
Fuel system	EFI
Starting system	Electric
Clutch	Automatic CVT
Transmission	Belt

Chassis

Front suspension	Telescopic forks
Rear suspension	Telescopic coil spring oil damped
Front tyre	90/90-12
Rear tyre	100/80-12
Front brake	Disc ø190mm
Rear brake	Disc ø220mm

Available Colours:

Dimensions

Overall L*W*H	2005*685*1160mm
Wheel base	1345mm
Seat height	770mm
Ground clearance	120mm
Curb weight	128kg
Fuel capacity	7L

Homologation: E5+

QJMOTOR

RK0 125 S (QJ125T-6J)

SCOOTER



Engine

Type	1-Cylinder, 2V SOHC, Air-Cooled
Bore*Stroke	52.5*57.4mm
Displacement	124cc
Max.Horsepower	6.9KW/7000RPM
MAX.Torque	10NM/6000RPM
Fuel system	EFI
Starting system	Electric
Clutch	Dry Centrifugal
Transmission	Belt

Chassis

Front suspension	Telescopic forks
Rear suspension	Telescopic coil spring oil damped
Front tyre	90/90-12
Rear tyre	100/90-10
Front brake	Disc ø190mm
Rear brake	Disc ø225mm

Dimensions

Overall L*W*H	1904*860*1130mm
Wheel base	1354mm
Seat height	775mm
Ground clearance	135mm
Curb weight	119kg
Fuel capacity	6L

Available Colours:   

Homologation: N/A

QJMOTOR

RK0 125 P (QJ125T-6P)

SCOOTER



Engine

Type	1-Cylinder, 2V, SOHC, Air-cooled
Bore*Stroke	52.5*57.4mm
Displacement	124cc
Max.Horsepower	6.9KW/7000RPM
MAX.Torque	10.0NM/6000RPM
Fuel system	EFI
Starting system	Electric
Clutch	Dry Centrifugal
Transmission	Belt

Chassis

Front suspension	Telescopic
Rear suspension	Unit Swing
Front tyre	90/90-12
Rear tyre	100/80-12
Front brake	Hydraulic Disc ø190mm
Rear brake	Mechanical Drum ø130mm or Disc ø220mm (ABS)

Available Colours:   

Dimensions

Overall L*W*H	1906*685*1100mm
Wheel base	1319mm
Seat height	750mm
Ground clearance	120mm
Curb weight	113kg
Fuel capacity	6L

Homologation: E5+

QJMOTOR

MTX 125 (QJ125T-23H)

SCOOTER



Engine

Type	1-Cylinder, SOHC, Liquid-Cooled
Bore*Stroke	52.4*57.9mm
Displacement	125cc
Max.Horsepower	10.8KW/8750RPM
MAX.Torque	12.0NM/8250RPM
Fuel system	EFI
Starting system	Electric
Clutch	Automatic CVT
Transmission	Belt

Chassis

Front suspension	Telescopic forks
Rear suspension	Telescopic coil spring oil damped
Front tyre	110/80-14
Rear tyre	130/70-13
Front brake	Hydr.Disc (ABS)
Rear brake	Hydr.Disc (ABS)

Dimensions

Overall L*W*H	1945*765*1230mm
Wheel base	1335mm
Seat height	755mm
Ground clearance	140mm
Curb weight	132kg
Fuel capacity	8L

Available Colours:    

Homologation: 150: E-Mark
125: E5,E5+

QJMOTOR

ATR 125 (QJ125T-23F)

SCOOTER



Engine

Type	1-Cylinder, SOHC, Liquid-Cooled
Bore*Stroke	52.4*57.9mm
Displacement	125cc
Max.Horsepower	10.8KW/8750RPM
MAX.Torque	12.0NM/8250RPM
Fuel system	EFI
Starting system	Electric
Clutch	Automatic CVT
Transmission	Belt

Chassis

Front suspension	Telescopic forks
Rear suspension	Telescopic coil spring oil damped
Front tyre	110/80-14
Rear tyre	130/70-13
Front brake	Hydr.Disc(ABS)
Rear brake	Hydr.Disc(ABS)

Dimensions

Overall L*W*H	1975*770*1160mm
Wheel base	1345mm
Seat height	795mm
Ground clearance	165mm
Curb weight	132kg
Fuel capacity	8L

Available Colours:    

Homologation: 150: E-Mark
125: E5,E5+

QJMOTOR

FORT 125 N (QJ125T-5M)

/ SCOOTER



Engine

Type	1-Cylinder, SOHC, Liquid-Cooled
Bore*Stroke	52.4*57.9mm
Displacement	124.9cc
Max.Horsepower	10.8KW/8750RPM
MAX.Torque	12.0NM/8250RPM
Fuel system	EFI
Starting system	Electric
Clutch	Automatic CVT
Transmission	Belt

Chassis

Front suspension	Telescopic forks
Rear suspension	Telescopic coil spring oil damped
Front tyre	120-70-15
Rear tyre	140-70-14
Front brake	Disc ø256mm
Rear brake	Disc ø240mm

Dimensions

Overall L*W*H	2175*751*1380mm
Wheel base	1490mm
Seat height	780mm
Ground clearance	150mm
Curb weight	159kg
Fuel capacity	11.7L

Available Colours:   

Homologation: E5+

QJMOTOR

LTR 125 (QJ125T-27J)

SCOOTER



Engine

Type	1-Cylinder,SOHC,Liquid-Cooled
Bore*Stroke	52.4*57.9mm
Displacement	125cc
Max.Horsepower	10.8KW/8750RPM
MAX.Torque	12.0NM/8250RPM
Fuel system	EFI
Starting system	Electric
Clutch	Automatic
Transmission	Belt

Chassis

Front suspension	Telescopic forks
Rear suspension	Telescopic coil spring oil damped
Front tyre	100/90-12
Rear tyre	110/90-12
Front brake	Disc ø190mm(ABS)
Rear brake	Disc ø225mm(ABS)

Dimensions

Overall L*W*H	1900*710*1100mm
Wheel base	1300mm
Seat height	760mm
Ground clearance	120mm
Curb weight	118kg
Fuel capacity	6L

Available Colours:   

Homologation: E5+

QJMOTOR

LTS 125 S (QJ125T-13C)

SCOOTER



Engine

Type	1-Cylinder,SOHC,Forcedly Air-Cooled
Bore*Stroke	52.5*57.4mm
Displacement	124cc
Max.Horsepower	6.9KW/7000RPM
MAX.Torque	10.0NM/6000RPM
Fuel system	EFI
Starting system	Electric
Clutch	Automatic
Transmission	Automatic CVT

Chassis

Front suspension	Telescopic forks
Rear suspension	Telescopic coil spring oil damped
Front tyre	90/80-14
Rear tyre	100/80-14
Front brake	Disc ø240mm
Rear brake	Disc ø190mm

Dimensions

Overall L*W*H	1890*712*1100mm
Wheel base	1300mm
Seat height	760mm
Ground clearance	140mm
Curb weight	106kg
Fuel capacity	7L

Available Colours:  

Homologation: /

QJMOTOR

SQ 16 (QJ125T-30E)

SCOOTER



Engine

Type	1-Cylinder, Liquid-Cooled
Bore*Stroke	52.4*57.9mm
Displacement	125cc
Max.Horsepower	10.8KW/8750RPM
MAX.Torque	12.0NM/8250RPM
Fuel system	EFI
Starting system	Electric
Clutch	Automatic CVT
Transmission	Belt

Chassis

Front suspension	Telescopic forks
Rear suspension	Telescopic coil spring oil damped
Front tyre	100/80-16
Rear tyre	120/80-14 or 120/80-16
Front brake	Disc ø240mm
Rear brake	Disc ø240mm

Dimensions

Overall L*W*H	2101*733*1131mm
Wheel base	1353mm
Seat height	799mm
Ground clearance	146mm
Curb weight	134kg
Fuel capacity	7.8L

Available Colours:   

Homologation: E5, E5+

QJMOTOR

LTR 50 (QJ50T-27E)

SCOOTER



Engine

Type	1-Cylinder,SOHC,Air-Cooled
Bore*Stroke	37.0*46.4mm
Displacement	50cc
Max.Horsepower	2.1KW/6500RPM
MAX.Torque	3.5NM/5500RPM
Fuel system	EFI
Starting system	Electric
Clutch	Automatic
Transmission	Automatic CVT

Chassis

Front suspension	Telescopic forks
Rear suspension	Telescopic coil spring oil damped
Front tyre	100/80-12
Rear tyre	120/70-12
Front brake	Disc ø190mm
Rear brake	Drum ø110mm

Dimensions

Overall L*W*H	1885*695*1100
Wheel base	1300mm
Seat height	730mm
Ground clearance	120mm
Curb weight	105kg
Fuel capacity	6.2L

Available Colours:    

Homologation: E5

QJMOTOR

LTR 50 S (QJ50T-13C)

SCOOTER



Engine

Type	1-Cylinder, 2V SOHC,Air-Cooled
Bore*Stroke	37.0*46.4mm
Displacement	49.9cc
Max.Horsepower	2.8KW/8500RPM
MAX.Torque	3.5NM/6500RPM
Fuel system	EFI
Starting system	Electric
Clutch	Automatic CVT
Transmission	Belt

Chassis

Front suspension	Telescopic forks
Rear suspension	Telescopic coil spring oil damped
Front tyre	100/80-12
Rear tyre	120/70-12
Front brake	Disc ø190mm
Rear brake	Drum ø110mm

Dimensions

Overall L*W*H	1890*712*1110mm
Wheel base	1300mm
Seat height	760mm
Ground clearance	130mm
Curb weight	93kg
Fuel capacity	7L

Available Colours:  

Homologation: E5

QJMOTOR

Commute Series



QJMOTOR

TRX 25 (QJ250-29K)

COMMUTE



Engine

Type	1-Cylinder,SOHC,Liquid-Cooled
Bore*Stroke	72.0*61.2mm
Displacement	249.2cc
Max.Horsepower	20.5KW/9500RPM
MAX.Torque	22.5NM/7250RPM
Fuel system	EFI
Starting system	Electric
Clutch	Manual,multilate Wet Clutch
Transmission	6 Gears, Chain

Chassis

Front suspension	Telescopic Upside-Down
Rear suspension	Telescopic coil spring oil damped
Front tyre	100/80-17
Rear tyre	130/70-17
Front brake	Hydr.Disc ø260mm (ABS)
Rear brake	Hydr.Disc ø220mm (ABS)

Dimensions

Overall L*W*H	2065*810*1065mm
Wheel base	1360mm
Seat height	780mm
Ground clearance	190mm
Curb weight	155kg
Fuel capacity	13.5L

Available Colours:   

Homologation: 150/250: E-Mark
125: E5,E5+

QJMOTOR

TRX 12 (QJ125-29K)

COMMUTE



Engine

Type	1-Cylinder,SOHC,Air-cooled
Bore*Stroke	54.0*54.5mm
Displacement	125cc
Max.Horsepower	8.2KW/9500RPM
MAX.Torque	10.0NM/7000RPM
Fuel system	EFI
Starting system	Electric
Clutch	Manual,multilate Wet Clutch
Transmission	5 Gears, Chain

Chassis

Front suspension	Telescopic Upside-Down
Rear suspension	Telescopic coil spring oil damped
Front tyre	100/80-17
Rear tyre	130/70-17
Front brake	Hydr.Disc ø260mm (ABS)
Rear brake	Hydr.Disc ø240mm (ABS)

Dimensions

Overall L*W*H	2065*810*1065mm
Wheel base	1360mm
Seat height	780mm
Ground clearance	190mm
Curb weight	142kg
Fuel capacity	13.5L

Available Colours:   

Homologation: 150/250:E-mark
125:E5,E5+

QJMOTOR

KPV 200 U (QJ175-6B)

COMMUTE



Engine

Type	1-Cylinder, SOHC, Air-Cooled
Bore*Stroke	61.0*63.1mm
Displacement	184.4cc
Max.Horsepower	12.4KW/8000RPM
MAX.Torque	16.3NM/7000RPM
Fuel system	EFI
Starting system	Electric
Clutch	Wet multi-plate
Transmission	6 Gears, Chain

Chassis

Front suspension	Telescopic forks
Rear suspension	Telescopic coil spring oil damped
Front tyre	3.00-17
Rear tyre	110/80-17
Front brake	Disc/Drum
Rear brake	Disc/Drum

Dimensions

Overall L*W*H	1918*786*1015mm
Wheel base	1245mm
Seat height	772mm
Ground clearance	150mm
Curb weight	115kg
Fuel capacity	11.2L

Available Colours:   

Homologation: /

QJMOTOR

NX 200 X (QJ175-26U)

COMMUTE



Engine

Type	1-Cylinder,SOHC,Air-Cooled
Bore*Stroke	61.0*63.1mm
Displacement	184.4cc
Max.Horsepower	12.4KW/8000RPM
MAX.Torque	16.3NM/7000RPM
Fuel system	EFI or Carburetor
Starting system	Electric
Clutch	Wet multi-plate
Transmission	6 Gears, Chain

Chassis

Front suspension	Telescopic forks
Rear suspension	Centre shock absorption
Front tyre	90/90-17
Rear tyre	120/80-17
Front brake	Disc
Rear brake	Disc

Dimensions

Overall L*W*H	2090*790*1090mm
Wheel base	1348mm
Seat height	780mm
Ground clearance	200mm
Curb weight	125kg
Fuel capacity	16L

Available Colours:    

Homologation: /

QJMOTOR

NX 150 (QJ150-26E)

COMMUTE



Engine

Type	1-Cylinder, 2V SOHC, Air-Cooled
Bore*Stroke	57.0*58.0mm
Displacement	148cc
Max.Horsepower	9.0KW/8000RPM
MAX.Torque	11.0NM/6500RPM
Fuel system	EFI or Carburetor
Starting system	Electric
Clutch	Manual, multilate Wet Clutch
Transmission	5 Gears, Chain

Chassis

Front suspension	Telescopic forks
Rear suspension	Telescopic coil spring oil damped
Front tyre	90/90-17
Rear tyre	120/80-17
Front brake	Hydr.Disc ø240mm
Rear brake	Hydr.Disc ø190mm or Drum ø130mm

Dimensions

Overall L*W*H	2090*790*1090mm
Wheel base	1350mm
Seat height	760mm
Ground clearance	180mm
Curb weight	125kg
Fuel capacity	16L

Available Colours:     

Homologation: E-Mark

QJMOTOR

NX 150 X (QJ150-26U)

COMMUTE



Engine

Type	1-Cylinder, 2V SOHC, Air-Cooled
Bore*Stroke	57.3*57.8mm
Displacement	149cc
Max.Horsepower	9.2KW/8500RPM
MAX.Torque	12.5NM/6500RPM
Fuel system	EFI
Starting system	Electric
Clutch	Wet multi-plate
Transmission	5 Gears, Chain

Chassis

Front suspension	Positive shock absorption
Rear suspension	Centre shock absorption
Front tyre	90/90-17
Rear tyre	120/80-17
Front brake	Disc ø240mm
Rear brake	Disc

Dimensions

Overall L*W*H	2090*790*1090mm
Wheel base	1348mm
Seat height	780mm
Ground clearance	200mm
Curb weight	125kg
Fuel capacity	16L

Available Colours:    

Homologation: 184: N/A
150: N/A

QJMOTOR

KPV 152 (QJ150-6C)

COMMUTE



Engine

Type	1-Cylinder,SOHC,Air-Cooled
Bore*Stroke	57.3*57.8mm
Displacement	149cc
Max.Horsepower	9.2KW/8500RPM
MAX.Torque	12.5NM/6500RPM
Fuel system	EFI
Starting system	Electric
Clutch	Wet multi-plate
Transmission	5 Gears,Chain

Chassis

Front suspension	Telescopic forks
Rear suspension	Telescopic coil spring oil damped
Front tyre	3.00-17 Tube
Rear tyre	110/80-17 Tube
Front brake	Disc ø220mm
Rear brake	Drum ø130mm

Dimensions

Overall L*W*H	1918*786*1015mm
Wheel base	1245mm
Seat height	772mm
Ground clearance	150mm
Curb weight	115kg
Fuel capacity	11.2L

Available Colours: ☐

Homologation: /

QJMOTOR

Electric Series



QJMOTOR

OMO 07 (QJ10000DT)

ELECTRIC



Engine

Type	Central-motor,air-cooled
Rated Power	11000W
Top Speed	129km/h
Gradeability	29°
Battery Type	Lithium-Ion
Battery Voltage	96V
Battery Capacity	80Ah
Battery Weight	45kg
Standard Charging Current	12A
Endurance Range	115km(working condition)

Chassis

Front Suspension	Hydraulic shock absorber
Rear Suspension	Hydraulic shock absorber
Front Tyre	120/70 ZR 15
Rear Tyre	150/70 ZR 14
Front Brake	Hydr.Disc(ABS)
Rear Brake	Hydr.Disc(ABS)

Dimensions

Overall L*W*H	2220*780*1390mm
Wheel Base	1565mm
Seat Height	780mm
Ground Clearance	165mm
Curb Weight	226Kg
Number of Battery	1 unit
30-80% SOC Charging Time	3.5h

Available Colours:    

Homologation: E5

QJMOTOR

OMO 03 (QJ5000DT-3)

ELECTRIC



Engine

Type	Central-drive,air-cooled
Rated Power	5000W
Top Speed	99km/h
Gradeability	19°
Battery Type	Lithium-Ion
Battery Voltage	72V
Battery Capacity	67Ah
Battery Weight	28Kg
Standard Charging Current	15A
Endurance Range	125km(working condition)

Chassis

Front Suspension	Hydraulic shock absorber
Rear Suspension	Hydraulic shock absorber
Front Tyre	110/80-14
Rear Tyre	130/70-13
Front Brake	Hydr.Disc(ABS)
Rear Brake	Hydr.Disc(ABS)

Dimensions

Overall L*W*H	1975*770*1160
Wheel Base	1345mm
Seat Height	780mm
Ground Clearance	145mm
Curb Weight	142kg
Number of Battery	1 unit
30-80% SOC Charging Time	3h

Available Colours:   

Homologation: E5

QJMOTOR

0AO (QJ5000D)

ELECTRIC



Engine

Type	Central-motor,air-cooled
Rated Power	5000W
Top Speed	99km/h
Gradeability	27°
Battery Type	Lithium-Ion
Battery Voltage	72V
Battery Capacity	60Ah
Battery Weight	23Kg
Standard Charging Current	10A
Endurance Range	112Km

Chassis

Front Suspension	Hydraulic shock absorber
Rear Suspension	Hydraulic shock absorber
Front Tyre	100/80-17
Rear Tyre	130/70-17
Front Brake	Hydr.Disc(ABS)
Rear Brake	Hydr.Disc(ABS)

Dimensions

Overall L*W*H	2035*760*1100mm
Wheel Base	1380mm
Seat Height	780mm
Ground Clearance	140mm
Curb Weight	144Kg
Number of Battery	1 unit
30-80% SOC Charging Time	3h

Available Colours:   

Homologation: E5

QJMOTOR

0AO-PRO (QJ5000D-A)

ELECTRIC



Engine

Type	Permanent magnet synchronous motor
Rated Power	5000W
Top Speed	99km/h
Gradeability	27°
Battery Type	Lithium-Ion
Battery Voltage	72V
Battery Capacity	90Ah
Battery Weight	42Kg
Standard Charging Current	15A
Endurance Range	170Km

Chassis

Front Suspension	Hydraulic shock absorber
Rear Suspension	Hydraulic shock absorber
Front Tyre	100/80-17
Rear Tyre	130/70-17
Front Brake	Hydr.Disc(ABS)
Rear Brake	Hydr.Disc(ABS)

Dimensions

Overall L*W*H	2035*760*1090mm
Wheel Base	1390mm
Seat Height	780mm
Ground Clearance	140mm
Curb Weight	164Kg
Number of Battery	1 unit
30-80% SOC Charging Time	3h

Available Colours:   

Homologation: CCC

RJMOTOR

MOk

/ ELECTRIC



Engine

Type	Hub-motor
Rated Power	350W
Top Speed	30km/h
Gradeability	5°
Battery Type	Lithium-Ion
Battery Voltage	36V
Battery Capacity	8Ah
Battery Weight	2.5kg
Standard Charging Current	2A
Endurance Range	30km

Chassis

Front Suspension	Telescopic
Rear Suspension	Swingarm
Front Tyre	20x2.8
Rear Tyre	16x2.4
Front Brake	Hydr.Disc
Rear Brake	Hydr.Disc

Dimensions

Overall L*W*H	1330*570*790mm
Wheel Base	870mm
Seat Height	550mm
Ground Clearance	100mm
Curb Weight	18kg
Number of Battery	1 unit
30-80% SOC Charging Time	2h

Available Colours: ☐ ☒

Homologation: N/A

QJMOTOR

Q2 (QJ3000D-7)

ELECTRIC



Engine

Type	Central-motor,air-cooled
Rated Power	3000W
Top Speed	45km/h
Gradeability	26°
Battery Type	Lithium-Ion
Battery Voltage	60V
Battery Capacity	32Ah
Battery Weight	13kg
Standard Charging Current	10A
Endurance Range	75km(working condition)

Chassis

Front Suspension	Hydraulic shock absorber
Rear Suspension	Pneumatic shock absorber
Front Tyre	70/100-19
Rear Tyre	70/100-19
Front Brake	Hydr.Disc
Rear Brake	Hydr.Disc

Available Colours: ☐

Dimensions

Overall L*W*H	1960*765*1080mm
Wheel Base	1275mm
Seat Height	815mm
Ground Clearance	275mm
Curb Weight	63kg
Number of Battery	1 unit
30-80% SOC Charging Time	1.5h

Homologation: E5

QJMOTOR

G2 (QJ3000DT-3)

ELECTRIC



Engine

Type	Mid-Drive,Air-Cooled
Rated Power	3000W
Top Speed	80km/h
Gradeability	18°
Battery Type	Lithium-Ion
Battery Voltage	43.2V
Battery Capacity	52Ah(26*2); 70 Ah(35*2)
Battery Weight	18kg(9kg*2)
Standard Charging Current	10A
Endurance Range	104km

Chassis

Front Suspension	Hydraulic shock absorber
Rear Suspension	Hydraulic shock absorber
Front Tyre	90/90-12
Rear Tyre	100/80-12
Front Brake	Hydr.Disc(CBS)
Rear Brake	Hydr.Disc(CBS)

Available Colours:   

Dimensions

Overall L*W*H	1850*685*1080mm
Wheel Base	1310mm
Seat Height	747mm
Ground Clearance	139mm
Curb Weight	110kg
Number of Battery	2 units
30-80% SOC Charging Time	2h/3h

Homologation: E5

QJMOTOR

OMO-01+ (QJ3000DT-3B)

ELECTRIC



Engine

Type	Mid-Drive, water-cooled
Rated Power	3000W
Top Speed	95km/h
Gradeability	18°
Battery Type	Lithium-Ion
Battery Voltage	72V
Battery Capacity	60Ah
Battery Weight	23kg
Standard Charging Current	10A
Endurance Range	100km

Chassis

Front Suspension	Hydraulic shock absorber
Rear Suspension	Hydraulic shock absorber
Front Tyre	100/80-14
Rear Tyre	110/70-13
Front Brake	Hydr.Disc ABS+TCS
Rear Brake	Hydr.Disc ABS+TCS

Available Colours:   

Dimensions

Overall L*W*H	1890*685*1090mm
Wheel Base	1310mm
Seat Height	770mm
Ground Clearance	150mm
Curb Weight	125kg
Number of Battery	1 units
30-80% SOC Charging Time	3.5h

Homologation: CCC

QJMOTOR

OMO-01 C (QJ3000DT-3C)

ELECTRIC



Engine

Type	Wheel-motor,air-cooled
Rated Power	3000W
Top Speed	80km/h
Gradeability	18°
Battery Type	Lithium-Ion
Battery Voltage	74V
Battery Capacity	28Ah*2
Battery Weight	13.5kg*2
Standard Charging Current	10A
Endurance Range	120km

Chassis

Front Suspension	Hydraulic shock absorber
Rear Suspension	Hydraulic shock absorber
Front Tyre	90/90-12
Rear Tyre	100/80-12
Front Brake	Hydr.Disc
Rear Brake	Hydr.Disc

Available Colours:   

Dimensions

Overall L*W*H	1850*685*1080mm
Wheel Base	1325mm
Seat Height	747mm
Ground Clearance	130mm
Curb Weight	117kg
Number of Battery	2 units
30-80% SOC Charging Time	2.5h

Homologation: CCC

QJMOTOR

ELT-27 E (QJ3000DT-27E)

ELECTRIC



Engine

Type	Hub-motor, air-cooled
Rated Power	3000W
Top Speed	80km/h
Gradeability	19°
Battery Type	Lithium-Ion
Battery Voltage	74V
Battery Capacity	28Ah*2
Battery Weight	13.5kg*2
Standard Charging Current	5A
Endurance Range	120km

Chassis

Front Suspension	Telescopic forks
Rear Suspension	Telescopic coil spring oil damped
Front Tyre	100/90-12
Rear Tyre	110/90-12
Front Brake	Disc ø220mm
Rear Brake	Disc ø180mm

Dimensions

Overall L*W*H	1890*690*1115mm
Wheel Base	1308mm
Seat Height	760mm
Ground Clearance	145mm
Curb Weight	115kg
Number of Battery	2 units
30-80% SOC Charging Time	5-6h

Available Colours: 

Homologation: N/A

QJMOTOR

ELT-27 K (QJ3000DT-27K)

ELECTRIC



Engine

Type	Hub-motor, air-cooled
Rated Power	3000W
Top Speed	80km/h
Gradeability	19°
Battery Type	Lithium-Ion
Battery Voltage	74V
Battery Capacity	28Ah*2
Battery Weight	13.5kg*2
Standard Charging Current	5A
Endurance Range	120km

Chassis

Front Suspension	Telescopic forks
Rear Suspension	Telescopic coil spring oil damped
Front Tyre	90/90-12
Rear Tyre	100/80-12
Front Brake	Disc ø220mm
Rear Brake	Disc ø190mm

Available Colours: /

Dimensions

Overall L*W*H	1912*692*1185mm
Wheel Base	1294mm
Seat Height	770mm
Ground Clearance	140mm
Curb Weight	118kg
Number of Battery	2 units
30-80% SOC Charging Time	5-6h

Homologation: N/A

QJMOTOR

E-LTS (QJ3000DT-13C)

ELECTRIC



Engine

Type	Wheel-motor,air-cooled
Rated Power	3000W
Top Speed	80km/h
Gradeability	18°
Battery Type	Lithium-lon
Battery Voltage	74V
Battery Capacity	28Ah*2
Battery Weight	13.5kg*2
Standard Charging Current	5A
Endurance Range	120km

Chassis

Front Suspension	Hydraulic shock absorber
Rear Suspension	Hydraulic shock absorber
Front Tyre	90/80-14
Rear Tyre	100/80-14
Front Brake	Hydr.Disc
Rear Brake	Hydr.Disc

Dimensions

Overall L*W*H	1887*772*1261mm
Wheel Base	1310mm
Seat Height	770mm
Ground Clearance	156mm
Curb Weight	110kg
Number of Battery	2 units
30-80% SOC Charging Time	3h

Available Colours: 

Homologation: N/A

QJMOTOR

E-KVP (QJ3000D-2)

ELECTRIC



Engine

Type	Central-drive, air-cooled
Rated Power	4000W
Top Speed	80km/h
Gradeability	24°
Battery Type	Lithium-Ion
Battery Voltage	72V
Battery Capacity	48Ah
Battery Weight	30kg
Standard Charging Current	5A
Endurance Range	80km

Chassis

Front Suspension	Telescopic forks
Rear Suspension	Telescopic coil spring oil damped
Front Tyre	110/80-17
Rear Tyre	3.0-17
Front Brake	Disc ø230mm
Rear Brake	Disc ø190mm

Dimensions

Overall L*W*H	1967*785*1155mm
Wheel Base	1256mm
Seat Height	854mm
Ground Clearance	200mm
Curb Weight	130kg
Number of Battery	1 unit
30-80% SOC Charging Time	5H

Available Colours:    

Homologation: N/A

QJMOTOR

TQ (QJ1500DT-5A)

ELECTRIC



Engine

Type	Hub-motor
Rated Power	1500W
Top Speed	55km/h
Gradeability	12°
Battery Type	Lead-acid
Battery Voltage	72V
Battery Capacity	32Ah
Battery Weight	54kg
Standard Charging Current	3A
Endurance Range	95km

Chassis

Front Suspension	Hydraulic shock absorber
Rear Suspension	Hydraulic shock absorber
Front Tyre	90/90-12
Rear Tyre	90/90-10
Front Brake	Disc
Rear Brake	Disc

Dimensions

Overall L*W*H	1925*725*1145mm
Wheel Base	1355mm
Seat Height	730mm
Ground Clearance	155mm
Curb Weight	123kg
Number of Battery	6 units
30-80% SOC Charging Time	4h

Available Colours:

Homologation: CCC

QJMOTOR

DQ (QJ1000DT-7)

ELECTRIC



Engine

Type	Hub-motor
Rated Power	1000W
Top Speed	51km/h
Gradeability	12°
Battery Type	Lead-acid
Battery Voltage	60V
Battery Capacity	20Ah
Battery Weight	30kg
Standard Charging Current	10A
Endurance Range	50km

Chassis

Front Suspension	Hydraulic shock absorber
Rear Suspension	Hydraulic shock absorber
Front Tyre	3.00-10
Rear Tyre	3.00-10
Front Brake	Disc
Rear Brake	Drum

Dimensions

Overall L*W*H	1750*690*1086mm
Wheel Base	1270mm
Seat Height	755mm
Ground Clearance	140mm
Curb Weight	97kg
Number of Battery	5 unit
30-80% SOC Charging Time	3h

Available Colours: 

Homologation: CCC

QJMOTOR

BQ (QJ800DQT-D)

ELECTRIC



Engine

Type	Hub-motor
Rated Power	800W/1200W
Top Speed	45km/h
Gradeability	12°
Battery Type	Lithium-Ion
Battery Voltage	60V
Battery Capacity	20Ah/26Ah
Battery Weight	7kg/9kg
Standard Charging Current	10A
Endurance Range	65km

Chassis

Front Suspension	Hydraulic shock absorber
Rear Suspension	Hydraulic shock absorber
Front Tyre	60/100-10
Rear Tyre	60/100-10
Front Brake	Disc
Rear Brake	Disc

Dimensions

Overall L*W*H	1666*670*1050mm
Wheel Base	1227mm
Seat Height	730mm
Ground Clearance	180mm
Curb Weight	90kg
Number of Battery	1 unit
30-80% SOC Charging Time	3h

Available Colours:   

Homologation: CCC

RJMOTOR

V1 (TDT030Z)

ELECTRIC



Engine

Type	Hub-motor
Rated Power	400W
Top Speed	25km/h
Gradeability	6°
Battery Type	Lead-acid
Battery Voltage	48V
Battery Capacity	16Ah
Battery Weight	20kg
Standard Charging Current	3A
Endurance Range	60km

Chassis

Front Suspension	Hydraulic shock absorber
Rear Suspension	Hydraulic shock absorber
Front Tyre	60/100-10
Rear Tyre	60/100-10
Front Brake	Drum
Rear Brake	Drum

Dimensions

Overall L*W*H	1470*640*980mm
Wheel Base	1060mm
Seat Height	730mm
Ground Clearance	140mm
Curb Weight	≤55kg
Number of Battery	4 unit
30-80% SOC Charging Time	3h

Available Colours:    

Homologation: CCC

QJMOTOR

V2 (TDT031Z)

ELECTRIC



Engine

Type	Hub-motor
Rated Power	400W
Top Speed	25km/h
Gradeability	6°
Battery Type	Lead-acid
Battery Voltage	48V
Battery Capacity	16Ah
Battery Weight	20kg
Standard Charging Current	3A
Endurance Range	60km

Chassis

Front Suspension	Hydraulic shock absorber
Rear Suspension	Hydraulic shock absorber
Front Tyre	60/100-10
Rear Tyre	60/100-10
Front Brake	Drum
Rear Brake	Drum

Dimensions

Overall L*W*H	1485*662*1014mm
Wheel Base	1042mm
Seat Height	730mm
Ground Clearance	140mm
Curb Weight	≤55kg
Number of Battery	4 unit
30-80% SOC Charging Time	3h

Available Colours:    

Homologation: CCC

QJMOTOR

V3 (TDT040Z)

ELECTRIC



Engine

Type	Hub-motor
Rated Power	400W
Top Speed	25km/h
Gradeability	8°
Battery Type	Lithium-Ion
Battery Voltage	48V
Battery Capacity	24Ah
Battery Weight	7.6kg
Standard Charging Current	3A
Endurance Range	70km

Chassis

Front Suspension	Hydraulic shock absorber
Rear Suspension	Hydraulic shock absorber
Front Tyre	3.00-8
Rear Tyre	80/70-8
Front Brake	Drum
Rear Brake	Drum

Dimensions

Overall L*W*H	1570*675*1040mm
Wheel Base	1155mm
Seat Height	725mm
Ground Clearance	120mm
Curb Weight	≤55kg
Number of Battery	1 unit
30-80% SOC Charging Time	4h

Available Colours: 

Homologation: CCC

QJMOTOR

VO (TDT007Z/TDT008Z)

ELECTRIC



Engine

Type	Hub-motor
Rated Power	400W
Top Speed	25km/h
Gradeability	12°
Battery Type	Lead-acid or Lithium-Ion
Battery Voltage	48V
Battery Capacity	12Ah(Pb)/20Ah(Li)
Battery Weight	15.2kg(Pb)/9.6kg(Li)
Standard Charging Current	3A
Endurance Range	45km(Pb)/60km(Li)

Chassis

Front Suspension	Hydraulic shock absorber
Rear Suspension	Hydraulic shock absorber
Front Tyre	60/100-10
Rear Tyre	60/100-10
Front Brake	Drum
Rear Brake	Drum

Dimensions

Overall L*W*H	1545*666*1002mm
Wheel Base	1145mm
Seat Height	720mm
Ground Clearance	140mm
Curb Weight	≤55kg
Number of Battery	4 units(Pb)/1 unit(Li)
30-80% SOC Charging Time	3h

Available Colours:    

Homologation: CCC

QJMOTOR

VC (TDT024Z/TDT047Z)

ELECTRIC



Engine

Type	Hub-motor
Rated Power	400W
Top Speed	25km/h
Gradeability	12°
Battery Type	Lead-acid or Lithium-Ion
Battery Voltage	48V/60V(Pb)/48V(Li)
Battery Capacity	20Ah(Pb)/24Ah(Li)
Battery Weight	24kg(Pb)30kg(Pb)/8kg(Li)
Standard Charging Current	3A
Endurance Range	50km(Pb)/70km (Pb)/60km(Li)

Chassis

Front Suspension	Hydraulic shock absorber
Rear Suspension	Hydraulic shock absorber
Front Tyre	60/100-10
Rear Tyre	60/100-10
Front Brake	Drum
Rear Brake	Drum



Available Colours:



Dimensions

Overall L*W*H	1495*682*1020mm
Wheel Base	1142mm
Seat Height	725mm
Ground Clearance	150mm
Curb Weight	≤55kg
Number of Battery	4 units(Pb)/1 unit(Li)
30-80% SOC Charging Time	3h

Homologation: CCC

QJMOTOR

VC+ (TDT042Z/TDT059Z)

/ ELECTRIC



Engine

Type	Hub-motor
Rated Power	400W
Top Speed	25km/h
Gradeability	12°
Battery Type	Lead-acid or Lithium-Ion
Battery Voltage	48V/60V(Pb)/48V(Li)
Battery Capacity	20Ah(Pb)/24Ah(Li)
Battery Weight	24kg(Pb)/30kg(Pb)/8kg(Li)
Standard Charging Current	3A
Endurance Range	50km(Pb)/70km (Pb)/60km(Li)

Chassis

Front Suspension	Hydraulic shock absorber
Rear Suspension	Hydraulic shock absorber
Front Tyre	60/100-10
Rear Tyre	60/100-10
Front Brake	Drum
Rear Brake	Drum

Available Colours:    

Dimensions

Overall L*W*H	1540*744*1040mm
Wheel Base	1140mm
Seat Height	735mm
Ground Clearance	150mm
Curb Weight	≤55kg
Number of Battery	4 units(Pb)/1 unit(Li)
30-80% SOC Charging Time	3h

Homologation: CCC

QJMOTOR

S2 (TDR068Z/TDR027Z)

ELECTRIC



Engine

Type	Hub-motor
Rated Power	400W
Top Speed	25km/h
Gradeability	8°
Battery Type	Lead-acid or Lithium-Ion
Battery Voltage	48V
Battery Capacity	12Ah(Pb)/24Ah(Li)
Battery Weight	15.2kg(Pb)/7.6kg(Li)
Standard Charging Current	2A/3A
Endurance Range	35km

Chassis

Front Suspension	Hydraulic shock absorber
Rear Suspension	Hydraulic shock absorber
Front Tyre	3.00-10
Rear Tyre	3.00-10
Front Brake	Disc
Rear Brake	Drum

Dimensions

Overall L*W*H	1710*655*1060mm
Wheel Base	1235mm
Seat Height	710mm
Ground Clearance	160mm
Curb Weight	≤55kg
Number of Battery	4 units(Pb)/1 unit(Li)
30-80% SOC Charging Time	3h/4h

Available Colours: 

Homologation: CCC

RJMOTOR

S3 (TDR028Z)

ELECTRIC



Engine

Type	Hub-motor
Rated Power	400W
Top Speed	25km/h
Gradeability	8°
Battery Type	Lithium-Ion
Battery Voltage	48V
Battery Capacity	24Ah
Battery Weight	7.6kg
Standard Charging Current	3A
Endurance Range	70km

Chassis

Front Suspension	Hydraulic shock absorber
Rear Suspension	Hydraulic shock absorber
Front Tyre	3.00-10
Rear Tyre	3.00-10
Front Brake	Disc
Rear Brake	Drum

Dimensions

Overall L*W*H	1710*655*1060mm
Wheel Base	1235mm
Seat Height	700mm
Ground Clearance	150mm
Curb Weight	≤55kg
Number of Battery	1 unit
30-80% SOC Charging Time	4h

Available Colours:   

Homologation: CCC

QJMOTOR

S5 (TDR029Z)

ELECTRIC



Engine

Type	Hub-motor
Rated Power	400W
Top Speed	25km/h
Gradeability	8°
Battery Type	Lithium-Ion
Battery Voltage	48V
Battery Capacity	24Ah
Battery Weight	7.6kg
Standard Charging Current	3A
Endurance Range	70km

Chassis

Front Suspension	Hydraulic shock absorber
Rear Suspension	Hydraulic shock absorber
Front Tyre	3.00-10
Rear Tyre	3.00-10
Front Brake	Disc
Rear Brake	Drum

Dimensions

Overall L*W*H	1710*655*1060mm
Wheel Base	1235mm
Seat Height	700mm
Ground Clearance	150mm
Curb Weight	≤55kg
Number of Battery	1 unit
30-80% SOC Charging Time	4h

Available Colours:    

Homologation: CCC

QJMOTOR

S6 (TDT041Z)

ELECTRIC



Engine

Type	Hub-motor
Rated Power	400W
Top Speed	25km/h
Gradeability	8°
Battery Type	Lithium-Ion
Battery Voltage	48V
Battery Capacity	24Ah
Battery Weight	7.6kg
Standard Charging Current	3A
Endurance Range	70km

Chassis

Front Suspension	Hydraulic shock absorber
Rear Suspension	Hydraulic shock absorber
Front Tyre	2.75-10
Rear Tyre	2.75-10
Front Brake	Disc
Rear Brake	Disc

Dimensions

Overall L*W*H	1700*724*1065mm
Wheel Base	1240mm
Seat Height	720mm
Ground Clearance	150mm
Curb Weight	≤55kg
Number of Battery	1 unit
30-80% SOC Charging Time	4h

Available Colours:   

Homologation: CCC

RJMOTOR

MOi (TDR006Z)

ELECTRIC



Engine

Type	Hub-motor
Rated Power	400W
Top Speed	25km/h
Gradeability	8°
Battery Type	Lithium-Ion
Battery Voltage	48V
Battery Capacity	20Ah
Battery Weight	8.4kg
Standard Charging Current	3A
Endurance Range	60km

Chassis

Front Suspension	Telescopic 60mm
Rear Suspension	Swingarm 50mm
Front Tyre	2.25-12
Rear Tyre	2.25-12
Front Brake	Hydr.Disc
Rear Brake	Drum

Dimensions

Overall L*W*H	1660*660*1060mm
Wheel Base	1250mm
Seat Height	700mm
Ground Clearance	148mm
Curb Weight	55kg
Number of Battery	1 unit
30-80% SOC Charging Time	3h

Available Colours: 

Homologation: CCC

QJMOTOR

OMO 07 J (QJ10000DTJ)

ELECTRIC



Engine

Type	Central-motor,air-cooled
Rated Power	10000W
Top Speed	129km/h
Gradeability	29°
Battery Type	Lithium-Ion
Battery Voltage	96V
Battery Capacity	80Ah
Battery Weight	45kg
Standard Charging Current	12A
Endurance Range	115km(working condition)

Chassis

Front Suspension	Hydraulic shock absorber
Rear Suspension	Hydraulic shock absorber
Front Tyre	120/70 ZR 15
Rear Tyre	150/70 ZR 14
Front Brake	Hydr.Disc(ABS)
Rear Brake	Hydr.Disc(ABS)

Dimensions

Overall L*W*H	2280*990*1390mm
Wheel Base	1565mm
Seat Height	780mm
Ground Clearance	165mm
Curb Weight	236Kg
Number of Battery	1 unit
30-80% SOC Charging Time	3.5h

Available Colours:    

Homologation: CCC

QJMOTOR

OMO 03 J (QJ5000DTJ-3)

ELECTRIC



The picture status is different and needs to be updated

Engine

Type	Central-drive,air-cooled
Rated Power	5000W
Top Speed	99km/h
Gradeability	19°
Battery Type	Lithium-Ion
Battery Voltage	72V
Battery Capacity	67Ah
Battery Weight	28Kg
Standard Charging Current	15A
Endurance Range	125km(working condition)

Chassis

Front Suspension	Hydraulic shock absorber
Rear Suspension	Hydraulic shock absorber
Front Tyre	110/80-14
Rear Tyre	130/70-13
Front Brake	Hydr.Disc(ABS)
Rear Brake	Hydr.Disc(ABS)

Dimensions

Overall L*W*H	1975*770*1160
Wheel Base	1345mm
Seat Height	780mm
Ground Clearance	145mm
Curb Weight	160kg
Number of Battery	1 unit
30-80% SOC Charging Time	3h

Available Colours:   

Homologation: CCC (Single tail box status)

QJMOTOR

RainBOW

ELECTRIC



Engine

MMax.torque	113NM
Max.power	30KW
Top Speed	102km/h
Battery Type	Lithium Iron Phosphate
Battery Energy	17.3kwh
Endurance Range	201km

Chassis

Front Suspension	MacPherson type independent suspension
Rear Suspension	Trailing arm type drive axle
Front Tyre	145/80 R13
Rear Tyre	145/80 R13
Front wheelbase	1300mm
Rear wheelbase	1300mm

Dimensions

Overall L*W*H	3224*1515*1630mm
Wheel Base	2100mm
Fast charging time	0.5h
Slow charging time	6.5h

Available Colours:   

Homologation: /

RJMOTOR

SFT Series



QJMOTOR

SFT 900 (QJ900B)

/ SFT SERIES



Engine

Type	2-cylinder inline, 4-stroke, Liquid-cooled, 8V DOHC
Bore*Stroke	92.0*68.0mm
Displacement	904cc
Max.Horsepower	70.0KW/9000RPM
MAX.Torque	90.0NM/6500RPM
Fuel system	EFI
Starting system	Electric
Clutch	Wet multi-plate
Transmission	6 Gears, Chain

Chassis

Front suspension	Telescopic Upside-Down
Rear suspension	Telescopic coil spring oil damped
Front tyre	110/80 R19
Rear tyre	150/70 R17
Front brake	Disc ø320mm
Rear brake	Disc ø260mm

Dimensions

Overall L*W*H	2420*1735*1370mm
Wheel base	1550mm
Seat height	835mm
Ground clearance	180mm
Curb weight	385kg
Fuel capacity	24.0L

Available Colours:  

Homologation: /

QJMOTOR

SFT 600 (QJ500B-A)

SFT SERIES



Engine

Type	2-Cylinder inline, 8v DOHC, Liquid-Cooled
Bore*Stroke	70.5*71.0mm
Displacement	554cc
Max.Horsepower	41.2KW/8250RPM
MAX.Torque	54.0NM/5500RPM
Fuel system	EFI
Starting system	Electric
Clutch	Wet multi-plate
Transmission	6 Gears, Chain

Chassis

Front suspension	Telescopic forks
Rear suspension	Telescopic coil spring oil damped
Front tyre	130/90-16
Rear tyre	150/80-16
Front brake	Disc ø300mm
Rear brake	Disc ø250mm

Dimensions

Overall L*W*H	2285*1670*1150mm
Wheel base	1615mm
Seat height	770mm
Ground clearance	150mm
Curb weight	308kg
Fuel capacity	16L

Available Colours:   

Homologation: /

QJMOTOR

SFT 400 (QJ350B-B)

/ SFT SERIES



Engine

Type	V-Type 2-cylinder, 4-stroke, 8V DOHC, Liquid-cooled
Bore*Stroke	60.0*68.0mm
Displacement	385cc
Max.Horsepower	24.0KW/8000RPM
MAX.Torque	35.0NM/5000RPM
Fuel system	EFI
Starting system	Electric
Clutch	Wet multi-plate
Transmission	6 Gears, Chain

Chassis

Front suspension	Telescopic Upside-Down
Rear suspension	Telescopic coil spring oil damped
Front tyre	130/90-16
Rear tyre	150/80-16
Front brake	Disc ø300mm
Rear brake	Disc ø240mm

Dimensions

Overall L*W*H	2255*1645*1105mm
Wheel base	1550mm
Seat height	730mm
Ground clearance	150mm
Curb weight	278kg
Fuel capacity	16L

Available Colours:   

Homologation: /

QJMOTOR

SFT 300 (QJ300B)

SFT SERIES



Engine

Type	2-Cylinder V-Twin, 4V SOHC, Liquid-Cooled
Bore*Stroke	58.0*56.0mm
Displacement	296cc
Max.Horsepower	22.6KW/9000RPM
MAX.Torque	26.0NM/7000RPM
Fuel system	EFI
Starting system	Electric
Clutch	Wet multi-plate
Transmission	6 Gears,Chain

Chassis

Front suspension	Telescopic Upside-Down
Rear suspension	Telescopic coil spring oil damped
Front tyre	120/80-16
Rear tyre	150/80-15
Front brake	Disc ø280mm
Rear brake	Disc ø240mm

Dimensions

Overall L*W*H	2110*1660*1100mm
Wheel base	1400mm
Seat height	730mm
Ground clearance	150mm
Curb weight	265kg
Fuel capacity	13.5L

Available Colours:    

Homologation: /

RJMOTOR

Four Wheel Series



QJMOTOR

SFA 1000 (QJ1000A-A)

ATV SERIES



Engine

Type	2-Cylinder, 8V SOHC, Liquid-Cooled
Bore*Stroke	91.0*75.0mm
Displacement	976cc
Max.Horsepower	68.0KW/7300RPM
MAX.Torque	95.0NM/5500RPM
Fuel system	EFI
Starting system	Electric
Clutch	CVT Wet multi-plate
Transmission	CVT shaft

Chassis

Front suspension	Airbag shock absorber
Rear suspension	Pneumatic shock absorber
Front tyre	27*9-14
Rear tyre	27*11-14
Front brake	Disk ø210mm(double)
Rear brake	Disk ø210mm(double)

Dimensions

Overall L*W*H	2330*1274*1460mm
Wheel base	1480mm
Seat height	577mm
Ground clearance	285mm
Curb weight	490kg
Fuel capacity	25L

Available Colours:    

Homologation: EU167,EPA49

QJMOTOR

SFA 600 (QJ600A-B)

ATV SERIES



Engine

Type	1-Cylinder,DOHC,Liquid-Cooled
Bore*Stroke	99.0*75.0mm
Displacement	577cc
Max.Horsepower	36.0KW/7300RPM
MAX.Torque	55.0NM/5500RPM
Fuel system	EFI
Starting system	Electric
Clutch	CVT
Transmission	CVT shaft

Chassis

Front suspension	Oil damping
Rear suspension	Oil damping
Front tyre	25*8-12
Rear tyre	25*10-12
Front brake	Disk ø210mm(double)
Rear brake	Disk ø210mm(double)

Dimensions

Overall L*W*H	2330*1274*1460mm
Wheel base	1480mm
Seat height	577mm
Ground clearance	265mm
Curb weight	450kg
Fuel capacity	25L

Available Colours:    

Homologation: EU167,EPA49

QJMOTOR

SFA 500 (ATV 500)

ATV SERIES



Engine

Type	1-Cylinder,Liquid-Cooled
Bore*Stroke	99.0*63.4mm
Displacement	488cc
Max.Horsepower	30.0KW/7250RPM
MAX.Torque	45.0NM/6250RPM
Fuel system	EFI
Starting system	Electric
Clutch	Automatic
Transmission	L-H-N-R-P

Chassis

Front suspension	Oil damping
Rear suspension	Telescopic coil spring oil damped
Front tyre	25x8.00 12
Rear tyre	25x10.00 12
Front brake	Disc
Rear brake	Disc

Dimensions

Overall L*W*H	2240*1155*1335mm
Wheel base	1475mm
Seat height	520mm
Ground clearance	280mm
Curb weight	365kg
Fuel capacity	18L

Available Colours:   

Homologation: EU167

RJMOTOR

SFA 300 B (ATV 300)

ATV SERIES



Engine

Type	1-Cylinder, SOHC, Liquid-Cooled
Bore*Stroke	72.0*71.0mm
Displacement	289cc
Max.Horsepower	19.0KW/7500RPM
MAX.Torque	27.0NM/5500RPM
Fuel system	EFI
Starting system	Electric
Clutch	CVT
Transmission	L-H-N-R

Chassis

Front suspension	Telescopic coil spring oil damped
Rear suspension	Telescopic coil spring oil damped
Front tyre	AT24X8-10
Rear tyre	AT24X10-10
Front brake	Disc ø170mm
Rear brake	Disc ø180mm

Dimensions

Overall L*W*H	1930*1114*1295mm
Wheel base	1210mm
Seat height	525mm
Ground clearance	200mm
Curb weight	260kg
Fuel capacity	14L

Available Colours:    

Homologation: EU167

QJMOTOR

SFV 1000 (QJ1000US)

SSV SERIES



Engine

Type	2-Cylinder V-Type, 8V SOHC, Liquid-Cooled
Bore*Stroke	91.0*75.0mm
Displacement	976cc
Max.Horsepower	65.0KW/7250RPM
MAX.Torque	95.0NM/6250RPM
Fuel system	EFI
Starting system	Electric
Clutch	CVT
Transmission	L-H-N-R-P

Chassis

Front suspension	Electronic shock absorption
Rear suspension	Electronic shock absorption
Front tyre	32X10 R15
Rear tyre	32X10 R15
Front brake	Disc ø262mm
Rear brake	Disc ø248mm

Dimensions

Overall L*W*H	3350*1845*1750mm
Wheel base	2590mm
Seat height	302.4mm
Ground clearance	405mm
Curb weight	795kg
Fuel capacity	40L

Available Colours:  

Homologation: EPA/EU167

QJMOTOR

SFU 1000 R (QJ1000UU-A)

UTV SERIES



Engine

Type	2-Cylinder V,8VSOHC,Liquid-cooled
Bore*Stroke	91.0*75.0mm
Displacement	976cc
Max.Horsepower	65.0KW/7250RPM
MAX.Torque	95.0Nm/6250RPM
Fuel system	EFI
Starting system	Electric
Clutch	Automatic CVT
Transmission	L-H-N-R-P

Chassis

Front suspension	Double A-arms independent suspension
Rear suspension	Double A-arms independent suspension
Front tyre	27x9.00R14/30x9.00R14
Rear tyre	27x11.00R14/30x10.00R14
Front brake	Hydr.Disc ø260mm
Rear brake	Hydr.Disc ø240mm

Dimensions

Overall L*W*H	3110*1570*2015mm
Wheel base	2130mm
Seat height	480mm
Ground clearance	330/368mm
Curb weight	775kg
Fuel capacity	45L

Available Colours:  

Homologation: EU 167/EPA 49

QJMOTOR

SFU 1000 F (QJ1000UU)

UTV SERIES



Engine

Type	2-Cylinder V,8VSOHC,Liquid-cooled
Bore*Stroke	91.0*75.0mm
Displacement	976cc
Max.Horsepower	65.0KW/7250RPM
MAX.Torque	95.0Nm/6250RPM
Fuel system	EFI
Starting system	Electric
Clutch	Automatic CVT
Transmission	L-H-N-R-P

Chassis

Front suspension	Double A-arms independent suspension
Rear suspension	Double A-arms independent suspension
Front tyre	27x9.00R14/30x9.00R14
Rear tyre	27x11.00R14/30x10.00R14
Front brake	Hydr.Disc ø260mm
Rear brake	Hydr.Disc ø240mm

Dimensions

Overall L*W*H	3925*1570*2015mm
Wheel base	2945mm
Seat height	480mm
Ground clearance	330/368mm
Curb weight	895kg
Fuel capacity	45L

Available Colours:  

Homologation: EU 167/EPA 49

@QJMOTOR_GLOBAL



Facebook



Instagram



Tiktok



Youtube



GLOBAL.QJMOTOR.COM



IMD@QJMOTOR.COM